

屋内照明器具特性	
品番 (品名)	XLJ 4200J
光源	LED5000_92_6100 ×1 6100.0 lm
管理番号	K0173856 (0) DY 1
BZ分類	BZ4 / 0.9 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 9	0 . 6	5 9	4 8	4 0	3 5	5 8	4 7	4 0	3 5	5 6	4 6	4 0	3 5	5 4	4 5	3 9	3 5	3 3				
			0 . 8 7	0 . 8	7 1	6 1	5 4	4 8	7 0	6 0	5 3	4 8	6 7	5 9	5 3	4 8	6 5	5 7	5 2	4 8	4 6				
			0 . 8 3	1 . 0	7 8	6 9	6 3	5 8	7 7	6 8	6 2	5 7	7 4	6 7	6 1	5 7	7 2	6 6	6 1	5 7	5 5				
				1 . 2 5	8 5	7 7	7 0	6 6	8 3	7 6	7 0	6 5	8 1	7 4	6 9	6 5	7 8	7 3	6 8	6 5	6 3				
下方投影面積 等価発光面積		c m ²		1 . 5	8 9	8 1	7 6	7 1	8 7	8 1	7 5	7 1	8 4	7 9	7 4	7 0	8 2	7 7	7 3	7 0	6 8				
				2 . 0	9 4	8 8	8 3	7 9	9 2	8 7	8 3	7 9	9 0	8 5	8 1	7 8	8 7	8 3	8 0	7 7	7 5				
				2 . 5	9 7	9 2	8 8	8 4	9 5	9 1	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 4	8 2	8 0				
取付 高さ	器具間隔最大限			3 . 0	9 9	9 5	9 1	8 8	9 7	9 4	9 0	8 7	9 5	9 2	8 9	8 6	9 2	9 0	8 7	8 5	8 3				
	横方向 (A)	縦方向 (B)		4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 7				
H m	1 . 6 6 H m	1 . 6 6 H m		5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9				
				7 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2				
				1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4				

