

屋内照明器具特性	
品番 (品名)	XLGB1042
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0179040 (0) DR 1
BZ分類	BZ2 / 8.5 / BZ1

器具効率		62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	41	35	31	28	40	35	31	28	39	34	31	28	38	34	30	28	27
			0.63	0.8	48	42	39	36	47	42	39	36	46	41	38	36	44	41	38	36	35
			0.56	1.0	52	47	44	41	51	47	43	41	50	46	43	41	48	45	43	41	40
				1.25	55	51	48	45	54	50	48	45	53	50	47	45	51	49	46	45	44
下方投影面積		cm ²		1.5	57	53	51	48	56	53	50	48	55	52	50	48	53	51	49	47	46
			等価発光面積	cm ²	2.0	60	57	54	52	59	56	54	52	57	55	53	52	56	54	52	51
取付 高さ	器具間隔最大限			2.5	61	59	57	55	60	58	56	55	59	57	55	54	57	56	55	53	52
	横方向 (A) 縦方向 (B)			3.0	62	60	58	57	61	59	58	56	60	58	57	56	58	57	56	55	53
H m	1.28 H m 1.28 H m			4.0	63	62	60	59	63	61	60	59	61	60	59	58	60	59	58	57	55
				5.0	64	63	62	60	63	62	61	60	62	61	60	59	60	60	59	58	57
				7.0	65	64	63	62	64	63	62	62	63	62	61	61	61	61	60	60	58
				10.0	65	65	64	63	65	64	63	63	63	63	62	62	62	61	61	61	59

