

| 屋内照明器具特性 |                        |
|----------|------------------------|
| 品番 (品名)  | XLGB1048               |
| 光源       | LLD2000CU1 ×1 566.0 lm |
| 管理番号     | K0179045 ( 0 ) DR 1    |
| BZ分類     | BZ5 / 0.9 / BZ4        |

| 器具効率     |          | 94 %            | 反射率     | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |   |   |
|----------|----------|-----------------|---------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|---|---|
|          |          |                 |         | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |   |   |
|          |          |                 |         | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |   |   |
| 上方光束     |          | 1 %             | 室指数     | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z  | C | M |
| 下方光束     |          | 93 %            |         |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |    |   |   |
| 保守率      |          | 良<br>中<br>否     | 0.67    | 0.6           | 54   | 42 | 35 | 30 | 52   | 42 | 35 | 30 | 50   | 41 | 34 | 30 | 48   | 40 | 34 | 30 | 28  |    |   |   |
|          |          |                 | 0.63    | 0.8           | 63   | 53 | 46 | 40 | 62   | 52 | 45 | 40 | 59   | 51 | 45 | 40 | 57   | 50 | 44 | 40 | 38  |    |   |   |
|          |          |                 | 0.56    | 1.0           | 70   | 60 | 53 | 48 | 68   | 59 | 53 | 48 | 66   | 58 | 52 | 47 | 63   | 56 | 51 | 47 | 45  |    |   |   |
|          |          |                 |         | 1.25          | 76   | 67 | 60 | 55 | 74   | 66 | 60 | 55 | 71   | 64 | 59 | 55 | 69   | 63 | 58 | 54 | 52  |    |   |   |
| 下方投影面積   |          | cm <sup>2</sup> | 1.5     | 80            | 72   | 66 | 61 | 78 | 71   | 65 | 60 | 75 | 69   | 64 | 60 | 73 | 67   | 63 | 59 | 57 |     |    |   |   |
| 等価発光面積   |          | cm <sup>2</sup> | 2.0     | 85            | 79   | 73 | 69 | 83 | 78   | 73 | 69 | 81 | 76   | 71 | 68 | 78 | 74   | 70 | 67 | 65 |     |    |   |   |
| 取付<br>高さ | 器具間隔最大限  |                 | 2.5     | 88            | 83   | 78 | 74 | 87 | 82   | 78 | 74 | 84 | 80   | 76 | 73 | 82 | 78   | 75 | 72 | 70 |     |    |   |   |
|          | 横方向 (A)  |                 | 縦方向 (B) |               | 3.0  | 90 | 86 | 82 | 78   | 89 | 85 | 81 | 78   | 86 | 83 | 80 | 77   | 84 | 81 | 78 | 76  | 73 |   |   |
| H m      | 1.29 H m | 1.29 H m        | 4.0     | 93            | 90   | 86 | 84 | 92 | 89   | 86 | 83 | 89 | 86   | 84 | 82 | 87 | 85   | 82 | 80 | 78 |     |    |   |   |
|          |          |                 | 5.0     | 95            | 92   | 89 | 87 | 94 | 91   | 88 | 86 | 91 | 89   | 87 | 85 | 89 | 87   | 85 | 83 | 81 |     |    |   |   |
|          |          |                 | 7.0     | 97            | 95   | 93 | 91 | 95 | 93   | 92 | 90 | 93 | 91   | 90 | 88 | 91 | 89   | 88 | 87 | 84 |     |    |   |   |
|          |          |                 | 10.0    | 98            | 97   | 95 | 94 | 97 | 95   | 94 | 93 | 95 | 93   | 92 | 91 | 92 | 91   | 90 | 89 | 87 |     |    |   |   |

