

屋内照明器具特性	
品番 (品名)	XLGB1110
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176322(0)DR1
BZ分類	BZ3

器具効率	75%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	75%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	4.9	4.2	3.7	3.4	4.9	4.1	3.7	3.3	4.7	4.1	3.6	3.3	4.6	4.0	3.6	3.3	3.2
	中	0.63	0.8	5.6	4.9	4.4	4.0	5.5	4.8	4.4	4.0	5.3	4.8	4.3	4.0	5.2	4.7	4.3	4.0	3.9
	否	0.56	1.0	6.0	5.4	4.9	4.5	5.9	5.3	4.9	4.5	5.7	5.2	4.8	4.5	5.6	5.1	4.7	4.5	4.3
			1.25	6.4	5.8	5.4	5.0	6.3	5.7	5.3	5.0	6.1	5.6	5.3	5.0	5.9	5.5	5.2	4.9	4.8
下方投影面積			1.5	6.7	6.1	5.7	5.4	6.5	6.0	5.7	5.3	6.3	5.9	5.6	5.3	6.2	5.8	5.5	5.2	5.1
等価発光面積			2.0	7.0	6.6	6.2	5.9	6.9	6.5	6.1	5.9	6.7	6.3	6.0	5.8	6.5	6.2	5.9	5.7	5.6
取付高さ	器具間隔最大限		2.5	7.2	6.8	6.5	6.2	7.1	6.8	6.5	6.2	6.9	6.6	6.4	6.1	6.7	6.5	6.2	6.1	5.9
	横方向 (A)	縦方向 (B)	3.0	7.4	7.0	6.7	6.5	7.3	7.0	6.7	6.5	7.1	6.8	6.6	6.4	6.9	6.7	6.5	6.3	6.1
Hm	1.32Hm	1.32Hm	4.0	7.6	7.3	7.1	6.9	7.5	7.2	7.0	6.8	7.3	7.1	6.9	6.7	7.1	6.9	6.7	6.6	6.4
			5.0	7.7	7.5	7.3	7.1	7.6	7.4	7.2	7.0	7.4	7.2	7.1	6.9	7.2	7.1	6.9	6.8	6.6
			7.0	7.8	7.6	7.5	7.4	7.7	7.6	7.4	7.3	7.5	7.4	7.3	7.2	7.3	7.2	7.1	7.0	6.8
			10.0	7.9	7.8	7.7	7.6	7.8	7.7	7.6	7.5	7.6	7.5	7.4	7.4	7.4	7.4	7.3	7.2	7.0

