

屋内照明器具特性	
品番 (品名)	XLGB1134
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0179050 (0) DR1
BZ分類	BZ3/4.5/BZ4

器具効率		80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		1 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		79 %																						
保守率		良 中 否	0.67	0.6	51	43	38	34	50	43	38	34	49	42	37	34	47	41	37	34	32			
			0.63	0.8	59	51	46	42	58	50	45	42	56	49	45	41	54	48	44	41	40			
			0.56	1.0	63	56	51	47	62	55	51	47	60	54	50	47	58	53	49	46	45			
				1.25	67	61	56	52	66	60	56	52	64	59	55	52	62	58	54	51	50			
下方投影面積		cm ²		1.5	70	64	60	56	69	63	59	56	67	62	58	55	65	61	57	55	53			
				2.0	74	69	65	62	73	68	64	61	70	67	63	61	68	65	62	60	58			
等価発光面積		cm ²		2.5	76	72	68	65	75	71	68	65	73	69	67	64	71	68	66	63	62			
				3.0	78	74	71	68	76	73	70	68	74	72	69	67	72	70	68	66	64			
H	m	1.32 H	m	1.32 H	m	4.0	80	77	74	72	79	76	74	71	76	74	72	70	74	73	71	69	67	
						5.0	81	79	76	74	80	78	76	74	78	76	74	73	76	74	73	72	69	
						7.0	82	81	79	77	81	80	78	77	79	78	77	75	77	76	75	74	72	
						10.0	83	82	81	80	82	81	80	79	80	79	79	78	79	78	77	76	74	

