

屋内照明器具特性	
品番 (品名)	XLGB1234
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0179050 (0) DR1
BZ分類	BZ3 / 4.5 / BZ4

器具効率		80 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	51	43	38	34	50	43	38	34	49	42	37	34	47	41	37	34	32	
			0.63	0.8	59	51	46	42	58	50	45	42	56	49	45	41	54	48	44	41	40	
			0.56	1.0	63	56	51	47	62	55	51	47	60	54	50	47	58	53	49	46	45	
			1.25	67	61	56	52	66	60	56	52	64	59	55	52	62	58	54	51	50		
下方投影面積		cm ²	1.5	70	64	60	56	69	63	59	56	67	62	58	55	65	61	57	55	53		
			等価発光面積	cm ²	2.0	74	69	65	62	73	68	64	61	70	67	63	61	68	65	62	60	58
取付 高さ	器具間隔最大限			2.5	76	72	68	65	75	71	68	65	73	69	67	64	71	68	66	63	62	
	横方向 (A)		縦方向 (B)	3.0	78	74	71	68	76	73	70	68	74	72	69	67	72	70	68	66	64	
H m	1.32 H m		1.32 H m	4.0	80	77	74	72	79	76	74	71	76	74	72	70	74	73	71	69	67	
				5.0	81	79	76	74	80	78	76	74	78	76	74	73	76	74	73	72	69	
				7.0	82	81	79	77	81	80	78	77	79	78	77	75	77	76	75	74	72	
				10.0	83	82	81	80	82	81	80	79	80	79	79	78	79	78	77	76	74	

