

| 屋内照明器具特性 |                                         |
|----------|-----------------------------------------|
| 品番 (品名)  | XLGB1417                                |
| 光源       | LLD3000CU1 x1 795.0 lm                  |
| 管理番号     | K0185529 (0) DR1                        |
| BZ分類     | BZ4/0.7/BZ3/2.8/BZ2/4.5/BZ3<br>/6.0/BZ2 |

| 器具効率     |           | 72 %            | 反射率             | 天井           | 80 % |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |    |
|----------|-----------|-----------------|-----------------|--------------|------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|----|
|          |           |                 |                 | 壁            | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |    |
|          |           |                 |                 | 床            | 10 % |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |    |
| 上方光束     |           | 0 %             | 室指数             | 照明率 ( X0.01) |      |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z  | CM |
| 下方光束     |           | 72 %            |                 |              |      |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |    |    |
| 保守率      |           | 良<br>中<br>否     | 0.67            | 0.6          | 44   | 36  | 31 | 28 | 43   | 36 | 31 | 28 | 42   | 35 | 31 | 28 | 40   | 35 | 31 | 28 | 26  |    |    |
|          |           |                 | 0.63            | 0.8          | 52   | 45  | 40 | 37 | 51   | 45 | 40 | 37 | 50   | 44 | 40 | 37 | 48   | 43 | 39 | 36 | 35  |    |    |
|          |           |                 | 0.56            | 1.0          | 57   | 51  | 47 | 43 | 56   | 51 | 46 | 43 | 55   | 50 | 46 | 43 | 53   | 49 | 45 | 43 | 41  |    |    |
|          |           |                 |                 | 1.25         | 62   | 56  | 52 | 49 | 61   | 56 | 52 | 49 | 59   | 55 | 51 | 48 | 57   | 54 | 51 | 48 | 47  |    |    |
| 下方投影面積   |           | cm <sup>2</sup> |                 | 1.5          | 64   | 60  | 56 | 53 | 63   | 59 | 55 | 53 | 62   | 58 | 55 | 52 | 60   | 57 | 54 | 52 | 50  |    |    |
| 等価発光面積   |           |                 | cm <sup>2</sup> | 2.0          | 68   | 64  | 61 | 58 | 67   | 63 | 60 | 58 | 65   | 62 | 59 | 57 | 63   | 61 | 59 | 57 | 55  |    |    |
|          |           |                 |                 | 2.5          | 70   | 67  | 64 | 62 | 69   | 66 | 63 | 61 | 67   | 65 | 62 | 60 | 65   | 63 | 61 | 60 | 58  |    |    |
| 取付<br>高さ | 器具間隔最大限   |                 | 3.0             | 71           | 68   | 66  | 64 | 70 | 68   | 65 | 64 | 68 | 66   | 64 | 63 | 67 | 65   | 63 | 62 | 60 |     |    |    |
|          | 横方向 ( A ) |                 |                 | 縦方向 ( B )    |      | 4.0 | 73 | 71 | 69   | 67 | 72 | 70 | 68   | 67 | 70 | 68 | 67   | 66 | 68 | 67 | 66  | 65 | 63 |
| H m      | 1.22 H m  |                 | 1.22 H m        |              | 5.0  | 74  | 72 | 70 | 69   | 73 | 71 | 70 | 68   | 71 | 70 | 69 | 67   | 70 | 68 | 67 | 66  | 65 |    |
|          |           |                 |                 |              | 7.0  | 75  | 74 | 72 | 71   | 74 | 73 | 72 | 71   | 72 | 71 | 70 | 70   | 71 | 70 | 69 | 68  | 66 |    |
|          |           |                 |                 |              | 10.0 | 76  | 75 | 74 | 73   | 75 | 74 | 73 | 72   | 73 | 72 | 72 | 71   | 72 | 71 | 70 | 70  | 68 |    |

