

| 屋内照明器具特性 |                                         |
|----------|-----------------------------------------|
| 品番 (品名)  | XLGB1535                                |
| 光源       | LLD3000CU1 x1 795.0 lm                  |
| 管理番号     | K0182745 (0) DB1                        |
| BZ分類     | BZ4/0.7/BZ3/2.8/BZ2/4.5/BZ3<br>/6.0/BZ2 |

| 器具効率     |           | 73 %            | 反射率  | 天井           | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |    |
|----------|-----------|-----------------|------|--------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|----|
|          |           |                 |      | 壁            | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |    |
|          |           |                 |      | 床            | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |    |
| 上方光束     |           | 0 %             | 室指数  | 照明率 ( X0.01) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z | CM |
| 下方光束     |           | 73 %            |      |              |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |   |    |
| 保守率      |           | 良<br>中<br>否     | 0.67 | 0.6          | 45   | 37 | 32 | 28 | 44   | 37 | 32 | 28 | 43   | 36 | 31 | 28 | 41   | 35 | 31 | 28 | 27  |   |    |
|          |           |                 | 0.63 | 0.8          | 53   | 46 | 41 | 38 | 52   | 46 | 41 | 38 | 51   | 45 | 41 | 37 | 49   | 44 | 40 | 37 | 36  |   |    |
|          |           |                 | 0.56 | 1.0          | 59   | 52 | 48 | 44 | 58   | 52 | 47 | 44 | 56   | 51 | 47 | 44 | 54   | 50 | 46 | 44 | 42  |   |    |
|          |           |                 |      | 1.25         | 63   | 57 | 53 | 50 | 62   | 57 | 53 | 50 | 60   | 56 | 52 | 49 | 58   | 55 | 52 | 49 | 48  |   |    |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5  | 66           | 61   | 57 | 54 | 65 | 60   | 57 | 54 | 63 | 59   | 56 | 53 | 61 | 58   | 55 | 53 | 51 |     |   |    |
| 等価発光面積   |           | cm <sup>2</sup> | 2.0  | 69           | 65   | 62 | 59 | 68 | 65   | 62 | 59 | 66 | 63   | 61 | 58 | 65 | 62   | 60 | 58 | 56 |     |   |    |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5  | 71           | 68   | 65 | 63 | 70 | 67   | 65 | 62 | 68 | 66   | 64 | 62 | 67 | 65   | 63 | 61 | 59 |     |   |    |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0  | 73           | 70   | 67 | 65 | 72 | 69   | 67 | 65 | 70 | 68   | 66 | 64 | 68 | 66   | 65 | 63 | 61 |     |   |    |
| H m      | 1.22 H m  | 1.22 H m        | 4.0  | 74           | 72   | 70 | 68 | 73 | 71   | 70 | 68 | 72 | 70   | 68 | 67 | 70 | 68   | 67 | 66 | 64 |     |   |    |
|          |           |                 | 5.0  | 75           | 73   | 72 | 70 | 74 | 73   | 71 | 70 | 73 | 71   | 70 | 69 | 71 | 70   | 69 | 68 | 66 |     |   |    |
|          |           |                 | 7.0  | 76           | 75   | 74 | 73 | 75 | 74   | 73 | 72 | 74 | 73   | 72 | 71 | 72 | 71   | 70 | 70 | 68 |     |   |    |
|          |           |                 | 10.0 | 77           | 76   | 75 | 75 | 76 | 75   | 75 | 74 | 75 | 74   | 73 | 73 | 73 | 72   | 72 | 71 | 69 |     |   |    |

