

屋内照明器具特性	
品番 (品名)	XLGB1536
光源	LLD3000CU1 x1 795.0 lm
管理番号	K0182745 (0) DB1
BZ分類	BZ4/0.7/BZ3/2.8/BZ2/4.5/BZ3 /6.0/BZ2

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																ZCM
保守率		良 中 否	0.67	0.6	45	37	32	28	44	37	32	28	43	36	31	28	41	35	31	28	27
			0.63	0.8	53	46	41	38	52	46	41	38	51	45	41	37	49	44	40	37	36
			0.56	1.0	59	52	48	44	58	52	47	44	56	51	47	44	54	50	46	44	42
				1.25	63	57	53	50	62	57	53	50	60	56	52	49	58	55	52	49	48
下方投影面積		cm ²		1.5	66	61	57	54	65	60	57	54	63	59	56	53	61	58	55	53	51
			等価発光面積	cm ²	2.0	69	65	62	59	68	65	62	59	66	63	61	58	65	62	60	58
取付 高さ	器具間隔最大限			2.5	71	68	65	63	70	67	65	62	68	66	64	62	67	65	63	61	59
	横方向 (A) 縦方向 (B)			3.0	73	70	67	65	72	69	67	65	70	68	66	64	68	66	65	63	61
H m	1.22 H m	1.22 H m		4.0	74	72	70	68	73	71	70	68	72	70	68	67	70	68	67	66	64
				5.0	75	73	72	70	74	73	71	70	73	71	70	69	71	70	69	68	66
				7.0	76	75	74	73	75	74	73	72	74	73	72	71	72	71	70	70	68
				10.0	77	76	75	75	76	75	75	74	75	74	73	73	73	72	72	71	69

