

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XLGB1611                |
| 光源       | LLD2000VCE1 ×1 531.0 lm |
| 管理番号     | K0176322 ( 0 ) DR 1     |
| BZ分類     | BZ3                     |

| 器具効率             |                 | 75 %            | 反射率  | 天井   | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|------------------|-----------------|-----------------|------|------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                  |                 |                 |      | 壁    | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                  |                 |                 |      | 床    | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                  |                 |                 |      | 室指数  | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率              |                 | 良<br>中<br>否     | 0.67 | 0.6  | 49                | 42 | 37 | 34 | 49   | 41 | 37 | 33 | 47   | 41 | 36 | 33 | 46   | 40 | 36 | 33 | 32  |
|                  |                 |                 | 0.63 | 0.8  | 56                | 49 | 44 | 40 | 55   | 48 | 44 | 40 | 53   | 48 | 43 | 40 | 52   | 47 | 43 | 40 | 39  |
|                  |                 |                 | 0.56 | 1.0  | 60                | 54 | 49 | 45 | 59   | 53 | 49 | 45 | 57   | 52 | 48 | 45 | 56   | 51 | 47 | 45 | 43  |
|                  |                 |                 |      | 1.25 | 64                | 58 | 54 | 50 | 63   | 57 | 53 | 50 | 61   | 56 | 53 | 50 | 59   | 55 | 52 | 49 | 48  |
| 下方投影面積<br>等価発光面積 |                 | cm <sup>2</sup> |      | 1.5  | 67                | 61 | 57 | 54 | 65   | 60 | 57 | 53 | 63   | 59 | 56 | 53 | 62   | 58 | 55 | 52 | 51  |
|                  |                 |                 |      | 2.0  | 70                | 66 | 62 | 59 | 69   | 65 | 61 | 59 | 67   | 63 | 60 | 58 | 65   | 62 | 59 | 57 | 56  |
| 取付<br>高さ         | 器具間隔最大限         |                 |      | 2.5  | 72                | 68 | 65 | 62 | 71   | 68 | 65 | 62 | 69   | 66 | 64 | 61 | 67   | 65 | 62 | 61 | 59  |
|                  | 横方向 (A) 縦方向 (B) |                 |      |      | 3.0               | 74 | 70 | 67 | 65   | 73 | 70 | 67 | 65   | 71 | 68 | 66 | 64   | 69 | 67 | 65 | 63  |
| Hm               | 1.32Hm          | 1.32Hm          | 4.0  | 76   | 73                | 71 | 69 | 75 | 72   | 70 | 68 | 73 | 71   | 69 | 67 | 71 | 69   | 67 | 66 | 64 |     |
|                  |                 |                 | 5.0  | 77   | 75                | 73 | 71 | 76 | 74   | 72 | 70 | 74 | 72   | 71 | 69 | 72 | 71   | 69 | 68 | 66 |     |
|                  |                 |                 | 7.0  | 78   | 76                | 75 | 74 | 77 | 76   | 74 | 73 | 75 | 74   | 73 | 72 | 73 | 72   | 71 | 70 | 68 |     |
|                  |                 |                 | 10.0 | 79   | 78                | 77 | 76 | 78 | 77   | 76 | 75 | 76 | 75   | 74 | 74 | 74 | 74   | 73 | 72 | 70 |     |

