

| 屋内照明器具特性 |                        |
|----------|------------------------|
| 品番 (品名)  | XLGB1693               |
| 光源       | LLD2000CU1 ×1 566.0 lm |
| 管理番号     | K0179077 (0) DR1       |
| BZ分類     | BZ5/0.7/BZ4/1.8/BZ5    |

| 器具効率     |                     | 95 %<br><br>上方光束<br>7 %<br>下方光束<br>88 % | 反射率    | 天井   | 80 %             |     |    |    |    | 70 % |    |    |    |    | 50 % |    |    |    |    | 30 % |     |    |    |  | 0 % |
|----------|---------------------|-----------------------------------------|--------|------|------------------|-----|----|----|----|------|----|----|----|----|------|----|----|----|----|------|-----|----|----|--|-----|
|          |                     |                                         |        | 壁    | 70               | 50  | 30 | 10 | 70 | 50   | 30 | 10 | 70 | 50 | 30   | 10 | 70 | 50 | 30 | 10   | 0 % |    |    |  |     |
|          |                     |                                         |        | 床    | 10 %             |     |    |    |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |     |    |    |  | 0 % |
|          |                     |                                         |        | 室指数  | 照明率 ( X0.01) ZCM |     |    |    |    |      |    |    |    |    |      |    |    |    |    |      |     |    |    |  |     |
| 保守率      |                     | 良<br>中<br>否                             | 0.67   | 0.6  | 54               | 43  | 36 | 31 | 53 | 42   | 36 | 31 | 50 | 41 | 35   | 30 | 47 | 39 | 34 | 30   | 28  |    |    |  |     |
|          |                     |                                         | 0.63   | 0.8  | 64               | 53  | 46 | 41 | 62 | 52   | 45 | 40 | 59 | 50 | 44   | 40 | 56 | 48 | 43 | 39   | 36  |    |    |  |     |
|          |                     |                                         | 0.56   | 1.0  | 70               | 60  | 53 | 48 | 68 | 59   | 52 | 47 | 64 | 57 | 51   | 46 | 61 | 55 | 49 | 45   | 43  |    |    |  |     |
|          |                     |                                         |        | 1.25 | 75               | 66  | 60 | 54 | 73 | 65   | 59 | 54 | 70 | 63 | 57   | 53 | 66 | 60 | 55 | 52   | 49  |    |    |  |     |
| 下方投影面積   |                     | cm <sup>2</sup>                         |        | 1.5  | 79               | 71  | 65 | 59 | 77 | 69   | 64 | 59 | 73 | 67 | 62   | 57 | 69 | 64 | 60 | 56   | 53  |    |    |  |     |
|          |                     |                                         | 等価発光面積 |      | cm <sup>2</sup>  | 2.0 | 84 | 77 | 71 | 67   | 82 | 76 | 70 | 66 | 78   | 73 | 68 | 64 | 74 | 70   | 66  | 63 | 59 |  |     |
| 取付<br>高さ | 器具間隔最大限             |                                         | 2.5    | 87   | 81               | 76  | 72 | 85 | 80 | 75   | 71 | 81 | 76 | 72 | 69   | 77 | 73 | 70 | 67 | 63   |     |    |    |  |     |
|          | 横方向 ( A ) 縦方向 ( B ) |                                         |        | 3.0  | 89               | 84  | 80 | 76 | 87 | 82   | 78 | 75 | 83 | 79 | 76   | 72 | 79 | 76 | 73 | 70   | 67  |    |    |  |     |
| H m      | 1.29 H m            | 1.29 H m                                | 4.0    | 92   | 88               | 84  | 81 | 90 | 86 | 83   | 80 | 86 | 83 | 80 | 77   | 82 | 80 | 77 | 75 | 71   |     |    |    |  |     |
|          |                     |                                         | 5.0    | 94   | 90               | 87  | 84 | 92 | 89 | 86   | 83 | 88 | 85 | 83 | 80   | 84 | 82 | 80 | 78 | 74   |     |    |    |  |     |
|          |                     |                                         | 7.0    | 96   | 93               | 91  | 88 | 94 | 91 | 89   | 87 | 90 | 88 | 86 | 84   | 86 | 85 | 83 | 81 | 77   |     |    |    |  |     |
|          |                     |                                         | 10.0   | 98   | 96               | 94  | 92 | 96 | 94 | 92   | 90 | 92 | 90 | 89 | 87   | 88 | 87 | 86 | 84 | 80   |     |    |    |  |     |

