

屋内照明器具特性	
品番 (品名)	XLGB1710
光源	LLD40001CQ1 ×1 845.0 lm
管理番号	K0186480 (0) DR1
BZ分類	BZ5

器具効率		66 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				照明率 (X0.01) ZCM																					
保守率		良 中 否	0.67	0.6	36	28	23	19	35	28	23	19	33	27	22	19	32	26	22	19	17				
			0.63	0.8	43	35	30	26	42	34	29	26	39	33	29	25	37	32	28	25	23				
			0.56	1.0	47	40	35	31	46	39	34	30	43	38	33	30	41	36	32	29	27				
				1.25	51	44	39	36	50	44	39	35	47	42	38	35	45	40	37	34	32				
下方投影面積 等価発光面積		cm ² cm ²		1.5	54	48	43	39	52	47	42	39	50	45	41	38	47	43	40	37	35				
				2.0	58	53	48	45	56	52	48	44	54	50	46	43	51	48	45	42	40				
				2.5	60	56	52	49	59	55	51	48	56	53	50	47	54	51	48	46	44				
取付 高さ	器具間隔最大限		3.0	62	58	55	52	60	57	54	51	58	55	52	50	55	53	51	49	46					
	横方向 (A)	縦方向 (B)		64	61	58	56	63	60	57	55	60	58	55	53	58	56	54	52	49					
H m	1.17 H m	1.17 H m	4.0	64	61	58	56	63	60	57	55	60	58	55	53	58	56	54	52	49					
			5.0	65	63	60	58	64	62	59	57	61	59	58	56	59	57	56	54	52					
			7.0	67	65	63	61	65	64	62	60	63	61	60	59	61	59	58	57	54					
			10.0	68	67	65	64	67	65	64	63	64	63	62	61	62	61	60	59	57					

