

屋内照明器具特性	
品番 (品名)	XLGB1720
光源	LLD3000CU1 x1 795.0 lm
管理番号	K0179027 (0) DR1
BZ分類	BZ5

器具効率		78 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.67	0.6	42	32	26	22	41	32	26	21	39	30	25	21	36	29	24	21	19	
			0.63	0.8	50	40	34	29	48	40	33	29	46	38	33	29	43	37	32	28	26	
			0.56	1.0	55	46	40	35	53	45	39	34	50	43	38	34	48	42	37	33	31	
				1.25	59	51	45	40	58	50	45	40	55	48	43	39	52	46	42	39	36	
下方投影面積		cm ²	1.56	1.5	63	55	49	45	61	54	49	44	58	52	47	43	55	50	46	42	40	
等価発光面積				cm ²	2.0	67	61	56	51	65	60	55	51	62	57	53	50	59	55	52	48	46
取付高さ	器具間隔最大限				2.5	70	64	60	56	68	63	59	55	65	61	57	54	62	58	55	53	50
H m	横方向 (A)		縦方向 (B)	3.0	72	67	63	59	70	66	62	59	67	63	60	57	64	61	58	56	53	
	1.18 H m			1.18 H m		4.0	75	71	67	64	73	69	66	63	70	67	64	62	67	64	62	60
				5.0	76	73	70	67	75	72	69	66	71	69	67	64	69	66	64	63	59	
				7.0	78	76	73	71	76	74	72	70	73	72	70	68	71	69	68	66	63	
				10.0	80	78	76	74	78	76	75	73	75	74	72	71	72	71	70	69	66	

