

屋内照明器具特性	
品番 (品名)	XLGB1721
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0178766 (0) DR1
BZ分類	BZ1/1.1/BZ2

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	43	38	34	32	42	37	34	32	41	37	34	32	40	36	33	32	31
			0.63	0.8	48	43	40	37	47	43	40	37	46	42	39	37	45	41	39	37	36
			0.56	1.0	51	47	44	41	50	46	43	41	49	45	43	41	47	45	42	40	39
				1.25	54	50	47	45	53	49	47	45	51	48	46	44	50	47	45	44	42
下方投影面積		cm ²		1.5	56	52	49	47	55	51	49	47	53	50	48	46	52	49	47	46	45
				2.0	58	55	53	51	57	54	52	50	55	53	51	50	54	52	50	49	48
等価発光面積		cm ²		2.5	59	57	55	53	58	56	54	53	57	55	53	52	55	54	52	51	50
				3.0	60	58	56	55	59	57	56	54	58	56	55	53	56	55	54	53	51
H m	1.26 H m		1.26 H m	4.0	61	60	58	57	61	59	58	57	59	58	56	55	57	56	55	54	53
				5.0	62	61	60	58	61	60	59	58	60	59	58	57	58	57	56	56	54
				7.0	63	62	61	60	62	61	60	60	60	60	59	58	59	58	58	57	55
				10.0	64	63	62	62	63	62	61	61	61	60	60	59	59	59	59	58	56

