

屋内照明器具特性	
品番 (品名)	XLGB82820
光源	LED5000_70_140 ×1 140.0 lm
管理番号	K0169176 (0) DR 1
BZ分類	BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		2 9 % 7 1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	5 7	4 6	3 9	3 4	5 4	4 4	3 8	3 4	4 9	4 1	3 6	3 2	4 5	3 8	3 4	3 0	2 7	
			0 . 6	0 . 8	6 6	5 6	5 0	4 5	6 3	5 4	4 8	4 4	5 8	5 0	4 5	4 1	5 2	4 6	4 2	3 9	3 4	
			0 . 5 6	1 . 0	7 3	6 4	5 7	5 2	6 9	6 1	5 5	5 1	6 3	5 6	5 2	4 8	5 7	5 2	4 8	4 5	4 0	
			1 . 2 5	7 8	7 0	6 4	5 9	7 5	6 7	6 2	5 7	6 8	6 2	5 8	5 4	6 2	5 7	5 4	5 1	4 5		
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 2	7 4	6 9	6 4	7 8	7 2	6 6	6 2	7 1	6 6	6 2	5 8	6 5	6 1	5 7	5 5	4 8		
			2 . 0	8 7	8 1	7 6	7 2	8 3	7 7	7 3	6 9	7 5	7 1	6 8	6 5	6 9	6 5	6 3	6 0	5 3		
取付 高さ	器具間隔最大限		2 . 5	9 0	8 5	8 0	7 7	8 6	8 1	7 7	7 4	7 8	7 5	7 2	6 9	7 1	6 8	6 6	6 4	5 6		
	横方向 (A) 縦方向 (B)		3 . 0	9 2	8 7	8 3	8 0	8 8	8 4	8 0	7 7	8 0	7 7	7 4	7 2	7 3	7 0	6 8	6 7	5 8		
H m	0 . 6 0 H m	1 . 2 2 H m	4 . 0	9 4	9 1	8 8	8 5	9 0	8 7	8 4	8 2	8 2	8 0	7 8	7 6	7 5	7 3	7 2	7 0	6 1		
			5 . 0	9 6	9 3	9 0	8 8	9 2	8 9	8 7	8 5	8 4	8 2	8 0	7 8	7 6	7 5	7 3	7 2	6 3		
			7 . 0	9 8	9 5	9 3	9 2	9 3	9 2	9 0	8 8	8 5	8 4	8 3	8 1	7 8	7 7	7 6	7 5	6 5		
			1 0 . 0	9 9	9 7	9 6	9 5	9 5	9 3	9 2	9 1	8 7	8 6	8 5	8 4	7 9	7 8	7 8	7 7	6 7		

