

屋内照明器具特性

品番 (品名)		X L G E 5 3 0 0 S F																			
光源		L D A 4 L - H - E 1 7 / S / 4 × 1 4 4 0 . 0 l m																			
管理番号		K 0 1 5 8 8 4 3 (0) D B 1																			
B Z 分類		B Z 1 0																			
器具効率 上方光束 下方光束		2 8 % 1 5 % 1 3 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
			室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 0 . 6 3 中 0 . 6 否 0 . 5 6	0 . 6	1 1	8	5	4	1 0	7	5	3	8	5	4	2	6	4	3	2	0	
			0 . 8	1 3	1 0	7	5	1 2	9	7	5	1 0	7	5	4	7	5	4	3	1	
			1 . 0	1 5	1 1	9	7	1 3	1 0	8	6	1 1	8	6	5	8	6	5	4	1	
			1 . 2 5	1 6	1 3	1 1	9	1 5	1 2	1 0	8	1 2	9	8	6	9	7	6	5	2	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	1 8	1 4	1 2	1 0	1 6	1 3	1 1	9	1 3	1 1	9	7	1 0	8	7	6	3	
			2 . 0	1 9	1 6	1 4	1 2	1 7	1 5	1 3	1 1	1 4	1 2	1 0	9	1 1	9	8	7	4	
取付 高さ	器具間隔最大限		2 . 5	2 0	1 8	1 6	1 4	1 8	1 6	1 4	1 3	1 5	1 3	1 2	1 0	1 2	1 0	9	8	5	
	横方向 (A)	縦方向 (B)	3 . 0	2 1	1 9	1 7	1 5	1 9	1 7	1 5	1 4	1 6	1 4	1 3	1 1	1 2	1 1	1 0	9	5	
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	2 2	2 0	1 8	1 7	2 0	1 9	1 7	1 6	1 7	1 5	1 4	1 3	1 3	1 2	1 1	1 0	6	
			5 . 0	2 3	2 1	2 0	1 8	2 1	1 9	1 8	1 7	1 7	1 6	1 5	1 4	1 4	1 3	1 2	1 1	7	
			7 . 0	2 4	2 2	2 1	2 0	2 2	2 1	1 9	1 8	1 8	1 7	1 6	1 5	1 5	1 4	1 3	1 3	8	
			1 0 . 0	2 4	2 3	2 2	2 1	2 2	2 2	2 1	2 0	1 9	1 8	1 7	1 7	1 5	1 5	1 4	1 4	9	

