

屋内照明器具特性	
品番 (品名)	XLGB1018
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176338 (0) DR1
BZ分類	BZ3

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																ZCM
保守率		良 中 否	0.67	0.6	47	39	33	30	46	38	33	30	44	37	33	30	43	37	32	29	28
			0.63	0.8	55	47	42	38	54	47	42	38	52	46	41	38	50	45	41	38	36
			0.56	1.0	60	53	48	44	58	52	48	44	56	51	47	44	54	50	46	43	42
				1.25	64	58	53	50	62	57	53	49	60	56	52	49	58	54	51	48	47
下方投影面積		cm ²	1.5	66	61	57	53	65	60	56	53	63	59	55	52	61	57	54	52	50	
			2.0	70	65	62	59	69	65	61	58	66	63	60	58	64	61	59	57	55	
等価発光面積		cm ²	2.5	72	68	65	62	71	67	64	62	69	66	63	61	66	64	62	60	58	
			3.0	73	70	67	65	72	69	67	64	70	67	65	63	68	66	64	62	60	
Hm	1.25Hm	1.25Hm	4.0	75	73	70	68	74	72	70	68	72	70	68	66	70	68	67	65	63	
			5.0	76	74	72	71	75	73	71	70	73	71	70	69	71	70	68	67	65	
			7.0	78	76	75	73	77	75	74	72	74	73	72	71	72	71	70	70	67	
			10.0	79	78	76	75	78	77	76	75	76	75	74	73	74	73	72	71	69	

