

屋内照明器具特性	
品番 (品名)	XLGB1051
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0189910 (2) DR1
BZ分類	BZ4/6.0/BZ5

器具効率		81 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) Z CM																
上方光束 下方光束		3 % 78 %	室指数	0.6	48	39	33	29	47	39	33	29	45	38	32	29	43	37	32	28	27	
				0.8	56	48	42	38	55	47	41	37	53	46	41	37	50	44	40	37	35	
				1.0	61	53	48	43	60	53	47	43	57	51	46	43	55	50	45	42	40	
				1.25	66	59	53	49	64	58	53	49	62	56	52	48	59	54	50	47	45	
下方投影面積		cm ²	1.5	69	62	57	53	67	61	57	53	64	59	55	52	62	58	54	51	49		
				等価発光面積		cm ²	2.0	73	67	63	59	71	66	62	59	68	64	61	58	66	62	59
取付高さ	器具間隔最大限		2.5				75	71	67	63	74	70	66	63	71	67	64	61	68	65	63	60
	H m	横方向 (A)		縦方向 (B)		3.0	77	73	69	66	76	72	69	66	73	70	67	64	70	67	65	63
1.26 H m		1.26 H m		4.0	79	76	73	71	78	75	72	70	75	73	70	68	73	70	68	67	64	
				5.0	81	78	76	73	79	77	75	72	77	74	72	71	74	72	71	69	66	
				7.0	82	80	78	77	81	79	77	76	78	77	75	74	76	74	73	72	69	
				10.0	84	82	81	79	82	81	80	78	80	78	77	76	77	76	75	74	71	

