

| 屋内照明器具特性 |                        |
|----------|------------------------|
| 品番 (品名)  | XLGB1071               |
| 光源       | LLD2000CU1 x1 566.0 lm |
| 管理番号     | K0190104 (1) DR1       |
| BZ分類     | BZ3                    |

| 器具効率     |           | 72 %            | 反射率  | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 %  |  |
|----------|-----------|-----------------|------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|------|--|
|          |           |                 |      | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 %  |  |
| 上方光束     |           | 1 %             |      | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 %  |  |
| 下方光束     |           | 71 %            | 室指数  | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    | Z CM |  |
| 保守率      |           | 良<br>中<br>否     | 0.67 | 0.6           | 46   | 38 | 33 | 30 | 45   | 38 | 33 | 30 | 43   | 37 | 33 | 30 | 42   | 36 | 32 | 30 | 28   |  |
|          |           |                 | 0.63 | 0.8           | 53   | 46 | 42 | 38 | 52   | 46 | 41 | 38 | 50   | 45 | 41 | 38 | 49   | 44 | 40 | 38 | 36   |  |
|          |           |                 | 1.0  | 58            | 52   | 47 | 44 | 57 | 51   | 47 | 44 | 55 | 50   | 46 | 43 | 53 | 49   | 46 | 43 | 42 |      |  |
|          |           |                 | 0.56 | 1.25          | 61   | 56 | 52 | 49 | 60   | 55 | 52 | 49 | 59   | 54 | 51 | 48 | 57   | 53 | 50 | 48 | 46   |  |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5  | 64            | 59   | 55 | 52 | 63 | 58   | 55 | 52 | 61 | 57   | 54 | 52 | 59 | 56   | 53 | 51 | 50 |      |  |
| 等価発光面積   |           | cm <sup>2</sup> | 2.0  | 67            | 63   | 60 | 57 | 66 | 62   | 59 | 57 | 64 | 61   | 59 | 56 | 62 | 60   | 58 | 56 | 54 |      |  |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5  | 69            | 66   | 63 | 61 | 68 | 65   | 62 | 60 | 66 | 64   | 61 | 59 | 64 | 62   | 60 | 59 | 57 |      |  |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0  | 71            | 68   | 65 | 63 | 70 | 67   | 64 | 62 | 68 | 65   | 63 | 62 | 66 | 64   | 62 | 61 | 59 |      |  |
| H m      | 1.33 H m  | 1.33 H m        | 4.0  | 72            | 70   | 68 | 66 | 71 | 69   | 67 | 66 | 69 | 68   | 66 | 65 | 68 | 66   | 65 | 64 | 62 |      |  |
|          |           |                 | 5.0  | 73            | 71   | 70 | 68 | 72 | 71   | 69 | 68 | 70 | 69   | 68 | 66 | 69 | 67   | 66 | 65 | 63 |      |  |
|          |           |                 | 7.0  | 74            | 73   | 72 | 70 | 73 | 72   | 71 | 70 | 72 | 71   | 70 | 69 | 70 | 69   | 68 | 67 | 65 |      |  |
|          |           |                 | 10.0 | 75            | 74   | 73 | 72 | 74 | 73   | 73 | 72 | 73 | 72   | 71 | 70 | 71 | 70   | 70 | 69 | 67 |      |  |

