

屋内照明器具特性	
品番 (品名)	XLGB1400
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0176189 (0) DR 1
BZ分類	BZ5

器具効率		71 % 上方光束 4 % 下方光束 67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	39	30	25	21	38	30	24	21	36	29	24	20	34	28	23	20	18
			0.63	0.8	46	38	32	28	45	37	31	28	42	36	31	27	40	34	30	27	25
			0.56	1.0	51	43	37	33	49	42	37	33	47	40	36	32	44	39	35	31	29
			1.25	55	48	42	38	53	47	42	38	51	45	41	37	48	43	39	36	34	
下方投影面積		cm ²	1.5	58	51	46	42	56	50	45	42	53	48	44	41	51	47	43	40	38	
等価発光面積			2.0	62	56	52	48	60	55	51	48	57	53	50	46	55	51	48	45	43	
取付	器具間隔最大限		2.5	64	60	56	52	63	59	55	52	60	56	53	50	57	54	52	49	47	
高さ	横方向 (A) 縦方向 (B)		3.0	66	62	58	55	65	61	58	55	62	59	56	53	59	57	54	52	49	
H m	1.17 H m	1.17 H m	4.0	68	65	62	60	67	64	61	59	64	62	59	57	62	60	58	56	53	
			5.0	70	67	65	62	68	66	64	62	66	64	62	60	63	61	60	58	55	
			7.0	72	69	68	66	70	68	66	65	68	66	64	63	65	64	62	61	58	
			10.0	73	71	70	69	71	70	69	67	69	68	67	66	66	65	65	64	61	

