

屋内照明器具特性	
品番 (品名)	XLGB1416
光源	LLD3000CU1 x1 795.0 lm
管理番号	K0182745 (0) DB1
BZ分類	BZ4/0.7/BZ3/2.8/BZ2/4.5/BZ3 /6.0/BZ2

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01)															
保守率		良 中 否	0.67	0.6	45	37	32	28	44	37	32	28	43	36	31	28	41	35	31	28	27	
			0.63	0.8	53	46	41	38	52	46	41	38	51	45	41	37	49	44	40	37	36	
			0.56	1.0	59	52	48	44	58	52	47	44	56	51	47	44	54	50	46	44	42	
				1.25	63	57	53	50	62	57	53	50	60	56	52	49	58	55	52	49	48	
下方投影面積		cm ²	等価発光面積 <td>1.5</td> <td>66</td> <td>61</td> <td>57</td> <td>54</td> <td>65</td> <td>60</td> <td>57</td> <td>54</td> <td>63</td> <td>59</td> <td>56</td> <td>53</td> <td>61</td> <td>58</td> <td>55</td> <td>53</td> <td>51</td>	1.5	66	61	57	54	65	60	57	54	63	59	56	53	61	58	55	53	51	
等価発光面積				cm ²	2.0	69	65	62	59	68	65	62	59	66	63	61	58	65	62	60	58	56
					2.5	71	68	65	63	70	67	65	62	68	66	64	62	67	65	63	61	59
取付高さ		器具間隔最大限			3.0	73	70	67	65	72	69	67	65	70	68	66	64	68	66	65	63	61
H m		1.22 H m	1.22 H m	4.0	74	72	70	68	73	71	70	68	72	70	68	67	70	68	67	66	64	
				5.0	75	73	72	70	74	73	71	70	73	71	70	69	71	70	69	68	66	
				7.0	76	75	74	73	75	74	73	72	74	73	72	71	72	71	70	70	68	
				10.0	77	76	75	75	76	75	75	74	75	74	73	73	73	72	72	71	69	

