

屋内照明器具特性	
品番 (品名)	XLGB1521
光源	LLD3000CU1 x1 795.0 lm
管理番号	K0178766 (0) DR 1
BZ分類	BZ1 / 1.1 / BZ2

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	43	38	34	32	42	37	34	32	41	37	34	32	40	36	33	32	31
			0.63	0.8	48	43	40	37	47	43	40	37	46	42	39	37	45	41	39	37	36
			1.0	51	47	44	41	50	46	43	41	49	45	43	41	47	45	42	40	39	
			0.56	1.25	54	50	47	45	53	49	47	45	51	48	46	44	50	47	45	44	42
下方投影面積		cm ²	1.5	56	52	49	47	55	51	49	47	53	50	48	46	52	49	47	46	45	
			2.0	58	55	53	51	57	54	52	50	55	53	51	50	54	52	50	49	48	
等価発光面積		cm ²	2.5	59	57	55	53	58	56	54	53	57	55	53	52	55	54	52	51	50	
			3.0	60	58	56	55	59	57	56	54	58	56	55	53	56	55	54	53	51	
Hm	1.26Hm	1.26Hm	4.0	61	60	58	57	61	59	58	57	59	58	56	55	57	56	55	54	53	
			5.0	62	61	60	58	61	60	59	58	60	59	58	57	58	57	56	56	54	
			7.0	63	62	61	60	62	61	60	60	60	60	59	58	59	58	58	57	55	
			10.0	64	63	62	62	63	62	61	61	61	60	60	59	59	59	59	58	56	

