

屋内照明器具特性	
品番 (品名)	XLX230DEN C
光源	LED5000_85_3200 ×1 3200.0 lm
管理番号	K0130919 (*) DB 1
BZ分類	BZ5

器具効率	100 % 上方光束 4 % 下方光束 96 %	反射率	天井 80 %				70 %				50 %				30 %				0 %
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数	照明率 (X0.01) ZCM																
保守率	良 0.83	0.6	55	42	34	29	53	42	34	29	51	40	33	28	48	39	33	28	26
	中 0.81	0.8	65	53	45	39	63	52	44	38	60	50	43	38	57	48	42	37	35
	否 0.77	1.0	71	60	52	46	69	59	51	46	66	57	50	45	62	55	49	44	42
		1.25	77	67	59	53	75	66	58	53	71	63	57	52	68	61	56	51	48
下方投影面積 等価発光面積	cm ² cm ²	1.5	81	72	65	59	79	70	64	58	75	68	62	57	72	66	60	56	53
		2.0	87	79	72	67	85	77	71	66	81	75	69	65	77	72	68	64	60
		2.5	90	84	78	73	88	82	77	72	85	79	74	70	81	76	72	69	66
取付高さ	器具間隔最大限		3.0	93	87	82	77	91	85	80	76	87	82	78	75	84	80	76	73
	横方向 (A)	縦方向 (B)	4.0	96	91	87	83	94	90	86	82	91	87	83	80	87	84	81	78
1.5m	1.94 m	1.96 m	5.0	98	94	90	87	96	93	89	86	93	89	86	84	89	87	84	82
2	2.58	2.58	7.0	101	97	95	92	99	96	93	91	95	93	90	88	92	90	88	86
2.5	3.23	3.2	10.0	102	100	98	96	101	99	96	95	97	95	94	92	94	92	91	90
3	3.89	3.83																	

