

| 屋内照明器具特性 |                                         |
|----------|-----------------------------------------|
| 品番 (品名)  | XLGB1537                                |
| 光源       | LLD3000CU1 ×1 795.0 lm                  |
| 管理番号     | K0185529 (0) DR1                        |
| BZ分類     | BZ4/0.7/BZ3/2.8/BZ2/4.5/BZ3<br>/6.0/BZ2 |

| 器具効率     |           | 72 %            | 反射率  | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |   |   |
|----------|-----------|-----------------|------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|---|---|
|          |           |                 |      | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |   |   |
|          |           |                 |      | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |   |   |
| 上方光束     |           | 0 %             | 室指数  | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | C | M |
| 下方光束     |           | 72 %            |      |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |   |   |
| 保守率      |           | 良<br>中<br>否     | 0.67 | 0.6           | 44   | 36 | 31 | 28 | 43   | 36 | 31 | 28 | 42   | 35 | 31 | 28 | 40   | 35 | 31 | 28 | 26  |  |   |   |   |
|          |           |                 | 0.63 | 0.8           | 52   | 45 | 40 | 37 | 51   | 45 | 40 | 37 | 50   | 44 | 40 | 37 | 48   | 43 | 39 | 36 | 35  |  |   |   |   |
|          |           |                 | 0.56 | 1.0           | 57   | 51 | 47 | 43 | 56   | 51 | 46 | 43 | 55   | 50 | 46 | 43 | 53   | 49 | 45 | 43 | 41  |  |   |   |   |
|          |           |                 |      | 1.25          | 62   | 56 | 52 | 49 | 61   | 56 | 52 | 49 | 59   | 55 | 51 | 48 | 57   | 54 | 51 | 48 | 47  |  |   |   |   |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5  | 64            | 60   | 56 | 53 | 63 | 59   | 55 | 53 | 62 | 58   | 55 | 52 | 60 | 57   | 54 | 52 | 50 |     |  |   |   |   |
| 等価発光面積   |           | cm <sup>2</sup> | 2.0  | 68            | 64   | 61 | 58 | 67 | 63   | 60 | 58 | 65 | 62   | 59 | 57 | 63 | 61   | 59 | 57 | 55 |     |  |   |   |   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5  | 70            | 67   | 64 | 62 | 69 | 66   | 63 | 61 | 67 | 65   | 62 | 60 | 65 | 63   | 61 | 60 | 58 |     |  |   |   |   |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0  | 71            | 68   | 66 | 64 | 70 | 68   | 65 | 64 | 68 | 66   | 64 | 63 | 67 | 65   | 63 | 62 | 60 |     |  |   |   |   |
| H m      | 1.22 H m  | 1.22 H m        | 4.0  | 73            | 71   | 69 | 67 | 72 | 70   | 68 | 67 | 70 | 68   | 67 | 66 | 68 | 67   | 66 | 65 | 63 |     |  |   |   |   |
|          |           |                 | 5.0  | 74            | 72   | 70 | 69 | 73 | 71   | 70 | 68 | 71 | 70   | 69 | 67 | 70 | 68   | 67 | 66 | 65 |     |  |   |   |   |
|          |           |                 | 7.0  | 75            | 74   | 72 | 71 | 74 | 73   | 72 | 71 | 72 | 71   | 70 | 70 | 71 | 70   | 69 | 68 | 66 |     |  |   |   |   |
|          |           |                 | 10.0 | 76            | 75   | 74 | 73 | 75 | 74   | 73 | 72 | 73 | 72   | 72 | 71 | 72 | 71   | 70 | 70 | 68 |     |  |   |   |   |

