

屋内照明器具特性	
品番 (品名)	XLGB1613
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0176313 (0) DR1
BZ分類	BZ3

器具効率		85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	56	47	41	38	55	47	41	38	53	46	41	37	51	45	41	37	36
			0.63	0.8	64	56	50	47	63	55	50	46	61	54	50	46	59	53	49	46	45
			0.56	1.0	69	62	57	53	68	61	56	53	66	60	56	52	64	59	55	52	50
				1.25	73	67	62	58	72	66	62	58	70	65	61	58	68	63	60	57	56
下方投影面積		cm ²		1.5	76	70	66	62	75	69	65	62	73	68	64	61	71	67	64	61	59
			等価発光面積	cm ²	2.0	80	75	71	68	79	74	71	68	76	73	70	67	74	71	69	66
取付 高さ	器具間隔最大限			2.5	82	78	75	72	81	77	74	71	79	76	73	71	77	74	72	70	68
	横方向 (A) 縦方向 (B)			3.0	84	80	77	75	82	79	77	74	80	78	75	73	78	76	74	72	70
H m	1.39 H m 1.39 H m			4.0	86	83	80	78	84	82	80	78	82	80	78	77	80	79	77	75	73
				5.0	87	85	83	81	86	84	82	80	84	82	80	79	82	80	79	78	75
				7.0	88	87	85	84	87	86	84	83	85	84	83	81	83	82	81	80	78
				10.0	89	88	87	86	88	87	86	85	86	85	84	83	84	83	83	82	80

