

屋内照明器具特性	
品番 (品名)	XLGB1685
光源	LLD2000CU1 x1 566.0 lm
管理番号	K0179072 (0) DR1
BZ分類	BZ3

器具効率		87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.67	0.6	56	48	42	38	55	47	42	38	54	46	41	38	52	45	41	38	36	
			0.63	0.8	65	57	51	47	64	56	51	47	62	55	50	47	60	54	50	47	45	
			0.56	1.0	70	63	57	54	69	62	57	53	67	61	56	53	65	60	56	53	51	
				1.25	75	68	63	59	73	67	63	59	71	66	62	59	69	65	61	58	57	
下方投影面積		cm ²		1.5	78	72	67	63	76	71	67	63	74	69	66	63	72	68	65	62	60	
等価発光面積			cm ²	2.0	81	77	73	69	80	76	72	69	78	74	71	68	76	73	70	68	66	
取付高さ	器具間隔最大限			2.5	84	80	76	73	83	79	76	73	80	77	74	72	78	76	73	71	69	
	横方向 (A)			縦方向 (B)	3.0	85	82	79	76	84	81	78	76	82	79	77	75	80	78	76	74	72
H m	1.40 H m	1.40 H m		4.0	88	85	82	80	86	84	81	79	84	82	80	78	82	80	79	77	75	
			5.0	89	86	84	82	88	85	84	82	85	84	82	80	83	82	80	79	77		
			7.0	90	88	87	85	89	87	86	85	87	86	84	83	85	84	83	82	79		
			10.0	91	90	89	88	90	89	88	87	88	87	86	85	86	85	84	84	81		

