

屋内照明器具特性	
品番 (品名)	XLGB1687
光源	LLD2000CU1 x1 566.0 lm
管理番号	K0179072 (0) DR 1
BZ分類	BZ3

器具効率		87 %	反射率	天井	80 %					70 %					50 %					30 %					0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %							
				床	10 %					10 %					10 %					10 %					0 %			
上方光束		1 %	室指数	照明率 (X0.01)																				Z	C		M	
下方光束		86 %																										
保守率		良 中 否	0.67	0.6	56	48	42	38	55	47	42	38	54	46	41	38	52	45	41	38	36							
			0.63	0.8	65	57	51	47	64	56	51	47	62	55	50	47	60	54	50	47	45							
			0.56	1.0	70	63	57	54	69	62	57	53	67	61	56	53	65	60	56	53	51							
				1.25	75	68	63	59	73	67	63	59	71	66	62	59	69	65	61	58	57							
下方投影面積		cm ²	1.5	78	72	67	63	76	71	67	63	74	69	66	63	72	68	65	62	60								
等価発光面積		cm ²	2.0	81	77	73	69	80	76	72	69	78	74	71	68	76	73	70	68	66								
取付 高さ	器具間隔最大限		2.5	84	80	76	73	83	79	76	73	80	77	74	72	78	76	73	71	69								
	横方向 (A)		縦方向 (B)		3.0	85	82	79	76	84	81	78	76	82	79	77	75	80	78	76	74	72						
H m	1.40 H m	1.40 H m	4.0	88	85	82	80	86	84	81	79	84	82	80	78	82	80	79	77	75								
			5.0	89	86	84	82	88	85	84	82	85	84	82	80	83	82	80	79	77								
			7.0	90	88	87	85	89	87	86	85	87	86	84	83	85	84	83	82	79								
			10.0	91	90	89	88	90	89	88	87	88	87	86	85	86	85	84	84	81								

