

屋内照明器具特性	
品番 (品名)	XLGB1696
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0179045 (0) DR 1
BZ分類	BZ5 / 0.9 / BZ4

器具効率		94 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	54	42	35	30	52	42	35	30	50	41	34	30	48	40	34	30	28
			0.63	0.8	63	53	46	40	62	52	45	40	59	51	45	40	57	50	44	40	38
			0.56	1.0	70	60	53	48	68	59	53	48	66	58	52	47	63	56	51	47	45
				1.25	76	67	60	55	74	66	60	55	71	64	59	55	69	63	58	54	52
下方投影面積		cm ²		1.5	80	72	66	61	78	71	65	60	75	69	64	60	73	67	63	59	57
			等価発光面積	cm ²	2.0	85	79	73	69	83	78	73	69	81	76	71	68	78	74	70	67
取付 高さ	器具間隔最大限			2.5	88	83	78	74	87	82	78	74	84	80	76	73	82	78	75	72	70
	横方向 (A) 縦方向 (B)			3.0	90	86	82	78	89	85	81	78	86	83	80	77	84	81	78	76	73
H m	1.29 H m	1.29 H m		4.0	93	90	86	84	92	89	86	83	89	86	84	82	87	85	82	80	78
				5.0	95	92	89	87	94	91	88	86	91	89	87	85	89	87	85	83	81
				7.0	97	95	93	91	95	93	92	90	93	91	90	88	91	89	88	87	84
				10.0	98	97	95	94	97	95	94	93	95	93	92	91	92	91	90	89	87

