

屋内照明器具特性	
品番 (品名)	XLGB82810
光源	LED5000_70_145 ×1 145.0 lm
管理番号	K0169174 (0) DR 1
BZ分類	BZ4 / 0.9 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		3 1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		6 9 %																					
保守率		良 中 否	0 . 6 3	0 . 6	5 5	4 4	3 7	3 2	5 2	4 2	3 6	3 1	4 7	3 9	3 3	2 9	4 2	3 6	3 1	2 8	2 4		
			0 . 6	0 . 8	6 5	5 4	4 7	4 2	6 1	5 2	4 6	4 1	5 5	4 8	4 3	3 9	5 0	4 4	3 9	3 6	3 1		
			0 . 5 6	1 . 0	7 1	6 2	5 5	5 0	6 7	5 9	5 3	4 8	6 1	5 4	4 9	4 5	5 5	4 9	4 5	4 2	3 7		
				1 . 2 5	7 7	6 8	6 2	5 7	7 3	6 5	5 9	5 5	6 6	6 0	5 5	5 1	5 9	5 5	5 1	4 8	4 1		
下方投影面積		c m ²		1 . 5	8 0	7 3	6 7	6 2	7 6	7 0	6 4	6 0	6 9	6 4	5 9	5 6	6 2	5 8	5 5	5 2	4 5		
等価発光面積			c m ²	2 . 0	8 5	7 9	7 4	7 0	8 1	7 6	7 1	6 7	7 4	6 9	6 5	6 2	6 6	6 3	6 0	5 8	5 0		
取付高さ	器具間隔最大限		2 . 5	8 9	8 3	7 9	7 5	8 4	8 0	7 6	7 2	7 6	7 3	6 9	6 7	6 9	6 6	6 4	6 1	5 3			
	横方向 (A)		縦方向 (B)	3 . 0	9 1	8 6	8 2	7 9	8 6	8 2	7 9	7 6	7 8	7 5	7 2	7 0	7 1	6 8	6 6	6 4	5 5		
H m	1 . 1 5 H m	1 . 2 5 H m	4 . 0	9 3	9 0	8 6	8 4	8 9	8 6	8 3	8 0	8 1	7 8	7 6	7 4	7 3	7 1	6 9	6 8	5 8			
			5 . 0	9 5	9 2	8 9	8 7	9 1	8 8	8 6	8 3	8 2	8 0	7 8	7 7	7 4	7 3	7 1	7 0	6 0			
			7 . 0	9 7	9 5	9 3	9 1	9 2	9 1	8 9	8 7	8 4	8 3	8 1	8 0	7 6	7 5	7 4	7 3	6 3			
			1 0 . 0	9 8	9 7	9 5	9 4	9 4	9 2	9 1	9 0	8 5	8 4	8 3	8 2	7 7	7 7	7 6	7 5	6 4			

