

屋内照明器具特性	
品番 (品名)	XLGB82900
光源	LED5000_70_360 ×1 360.0 lm
管理番号	K0171432 (0) DB1
BZ分類	BZ9/0.9/BZ8

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.63	0.6	44	32	24	18	40	29	22	17	33	24	18	14	26	20	15	11	6	
			0.6	0.8	53	40	32	26	48	37	30	24	39	31	25	20	31	25	20	16	9	
			0.56	1.0	59	47	38	32	54	43	35	30	44	36	30	25	35	29	24	20	12	
				1.25	64	53	45	38	59	49	41	35	48	41	35	30	39	33	28	24	15	
下方投影面積		cm ²	1.5	68	58	50	43	62	53	46	40	51	44	39	34	41	36	32	28	18		
			2.0	74	65	57	51	68	60	53	48	56	50	45	40	45	41	37	33	22		
取付 高さ	器具間隔最大限		2.5	78	70	63	57	71	64	58	53	59	54	49	45	48	44	40	37	25		
	横方向 (A)	縦方向 (B)	3.0	80	73	67	62	74	67	62	57	62	57	52	48	50	46	43	40	27		
H _m	1.59 H _m	2.09 H _m	4.0	84	78	72	68	77	72	67	63	65	61	57	54	53	50	47	44	30		
			5.0	86	81	76	72	79	75	71	67	67	63	60	57	55	52	50	47	33		
			7.0	89	85	81	78	82	79	75	72	69	67	64	62	57	55	53	51	36		
			10.0	91	88	85	82	84	82	79	77	72	69	67	65	60	58	56	55	39		

