

屋内照明器具特性	
品番 (品名)	XLGB82902
光源	LED2700_70_360 ×1 360.0 lm
管理番号	K0171432 (0) DB1
BZ分類	BZ9/0.9/BZ8

器具効率		100 % 上方光束 50 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
				室指数	照明率 (X0.01) Z CM																			
保守率		良 中 否	0.63	0.6	0.56	0.6	44	32	24	18	40	29	22	17	33	24	18	14	26	20	15	11	6	
			0.6	0.8	53	40	32	26	48	37	30	24	39	31	25	20	31	25	20	16	9			
			0.56	1.0	59	47	38	32	54	43	35	30	44	36	30	25	35	29	24	20	12			
			0.56	1.25	64	53	45	38	59	49	41	35	48	41	35	30	39	33	28	24	15			
下方投影面積		cm ²	1.5	68	58	50	43	62	53	46	40	51	44	39	34	41	36	32	28	24	18			
等価発光面積			cm ²	2.0	74	65	57	51	68	60	53	48	56	50	45	40	45	41	37	33	22			
取付高さ				器具間隔最大限			2.5	78	70	63	57	71	64	58	53	59	54	49	45	48	44	40	37	25
横方向 (A)				縦方向 (B)		3.0		80	73	67	62	74	67	62	57	62	57	52	48	50	46	43	40	27
H m	1.59 H m	2.09 H m		4.0	84			78	72	68	77	72	67	63	65	61	57	54	53	50	47	44	30	
			5.0		86			81	76	72	79	75	71	67	67	63	60	57	55	52	50	47	33	
					7.0		89	85	81	78	82	79	75	72	69	67	64	62	57	55	53	51	36	
						10.0	91	88	85	82	84	82	79	77	72	69	67	65	60	58	56	55	39	

