

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XLGB82905                  |
| 光源       | LED5000_70_220 x1 220.0 lm |
| 管理番号     | K0169179 ( 0 ) DR 1        |
| BZ分類     | BZ5 / 0.7 / BZ4            |

| 器具効率           |                     | 100 %               | 反射率    | 天井              | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------------|---------------------|---------------------|--------|-----------------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                |                     |                     |        | 壁               | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                |                     |                     |        | 床               | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                |                     |                     |        | 室指数             | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率            |                     | 良<br>中<br>否         | 0.63   | 0.6             | 50                | 39 | 32 | 27 | 47   | 37 | 30 | 26 | 39   | 32 | 26 | 23 | 33   | 27 | 23 | 20 | 15  |
|                |                     |                     | 0.6    | 0.8             | 60                | 49 | 42 | 37 | 55   | 46 | 39 | 35 | 47   | 40 | 35 | 31 | 39   | 34 | 30 | 27 | 21  |
|                |                     |                     |        | 1.0             | 66                | 56 | 49 | 44 | 61   | 53 | 46 | 42 | 52   | 46 | 41 | 37 | 44   | 39 | 35 | 32 | 25  |
|                |                     |                     | 0.56   | 1.25            | 72                | 63 | 56 | 51 | 66   | 59 | 53 | 48 | 57   | 51 | 46 | 43 | 48   | 43 | 40 | 37 | 29  |
| 下方投影面積         |                     | cm <sup>2</sup>     |        | 1.5             | 75                | 67 | 61 | 56 | 70   | 63 | 58 | 53 | 60   | 55 | 50 | 47 | 50   | 47 | 43 | 41 | 31  |
|                |                     |                     | 等価発光面積 | cm <sup>2</sup> | 2.0               | 81 | 74 | 69 | 64   | 75 | 69 | 64 | 60   | 64 | 60 | 56 | 53   | 54 | 51 | 48 | 46  |
| 取付高さ           | 器具間隔最大限             |                     |        | 2.5             | 84                | 78 | 73 | 69 | 78   | 73 | 69 | 65 | 67   | 63 | 60 | 57 | 56   | 54 | 51 | 49 | 38  |
|                | 横方向 (A) 縦方向 (B)     |                     |        | 3.0             | 86                | 81 | 77 | 73 | 80   | 76 | 72 | 69 | 69   | 66 | 63 | 60 | 58   | 56 | 54 | 52 | 39  |
| H <sub>m</sub> | 0.00 H <sub>m</sub> | 1.67 H <sub>m</sub> |        | 4.0             | 89                | 85 | 82 | 78 | 83   | 79 | 76 | 74 | 71   | 69 | 66 | 64 | 60   | 58 | 57 | 55 | 42  |
|                |                     |                     |        | 5.0             | 91                | 87 | 84 | 82 | 84   | 82 | 79 | 77 | 73   | 71 | 69 | 67 | 61   | 60 | 59 | 57 | 43  |
|                |                     |                     |        | 7.0             | 92                | 90 | 88 | 86 | 86   | 84 | 82 | 80 | 74   | 73 | 71 | 70 | 63   | 62 | 61 | 60 | 45  |
|                |                     |                     |        | 10.0            | 94                | 92 | 91 | 89 | 88   | 86 | 85 | 83 | 76   | 75 | 73 | 72 | 64   | 63 | 63 | 62 | 47  |

