

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XLGB82911                  |
| 光源       | LED3500_70_215 ×1 215.0 lm |
| 管理番号     | K0169180 ( 1 ) DR 1        |
| BZ分類     | BZ5 / 0.7 / BZ4            |

| 器具効率     |           | 100 %           | 反射率             | 天井            | 80 % |    |    |    |    | 70 % |    |    |    |    | 50 % |    |    |    |    | 30 % |     |  |  |      | 0 % |  |  |
|----------|-----------|-----------------|-----------------|---------------|------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|------|-----|--|--|------|-----|--|--|
|          |           |                 |                 | 壁             | 70   | 50 | 30 | 10 | 70 | 50   | 30 | 10 | 70 | 50 | 30   | 10 | 70 | 50 | 30 | 10   | 0 % |  |  |      |     |  |  |
|          |           |                 |                 | 床             | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |     |  |  |      | 0 % |  |  |
| 上方光束     |           | 50 %            | 室指数             | 照明率 ( X0.01 ) |      |    |    |    |    |      |    |    |    |    |      |    |    |    |    |      |     |  |  | Z CM |     |  |  |
| 下方光束     |           | 50 %            |                 |               |      |    |    |    |    |      |    |    |    |    |      |    |    |    |    |      |     |  |  |      |     |  |  |
| 保守率      |           | 良<br>中<br>否     | 0.63            | 0.6           | 50   | 39 | 32 | 27 | 46 | 36   | 30 | 25 | 39 | 32 | 26   | 23 | 33 | 27 | 23 | 20   | 15  |  |  |      |     |  |  |
|          |           |                 | 0.6             | 0.8           | 60   | 49 | 42 | 37 | 55 | 46   | 39 | 35 | 47 | 40 | 35   | 31 | 39 | 34 | 30 | 27   | 20  |  |  |      |     |  |  |
|          |           |                 |                 | 1.0           | 66   | 56 | 49 | 44 | 61 | 52   | 46 | 42 | 52 | 45 | 41   | 37 | 43 | 39 | 35 | 32   | 24  |  |  |      |     |  |  |
|          |           |                 | 0.56            | 1.25          | 71   | 63 | 56 | 51 | 66 | 59   | 53 | 48 | 56 | 51 | 46   | 43 | 47 | 43 | 40 | 37   | 28  |  |  |      |     |  |  |
| 下方投影面積   |           | cm <sup>2</sup> |                 | 1.5           | 75   | 67 | 61 | 56 | 70 | 63   | 57 | 53 | 59 | 54 | 50   | 47 | 50 | 46 | 43 | 41   | 31  |  |  |      |     |  |  |
| 等価発光面積   |           |                 | cm <sup>2</sup> | 2.0           | 80   | 74 | 69 | 64 | 75 | 69   | 64 | 60 | 64 | 60 | 56   | 53 | 54 | 51 | 48 | 46   | 35  |  |  |      |     |  |  |
| 取付<br>高さ | 器具間隔最大限   |                 |                 | 2.5           | 84   | 78 | 73 | 69 | 78 | 73   | 69 | 65 | 66 | 63 | 60   | 57 | 56 | 53 | 51 | 49   | 37  |  |  |      |     |  |  |
|          | 横方向 ( A ) |                 | 縦方向 ( B )       | 3.0           | 86   | 81 | 77 | 73 | 80 | 76   | 72 | 69 | 68 | 65 | 63   | 60 | 58 | 55 | 53 | 52   | 39  |  |  |      |     |  |  |
| H m      | 0.00 H m  | 1.67 H m        |                 | 4.0           | 89   | 85 | 81 | 78 | 83 | 79   | 76 | 74 | 71 | 68 | 66   | 64 | 60 | 58 | 56 | 55   | 41  |  |  |      |     |  |  |
|          |           |                 |                 | 5.0           | 90   | 87 | 84 | 82 | 84 | 81   | 79 | 77 | 72 | 70 | 68   | 67 | 61 | 60 | 58 | 57   | 43  |  |  |      |     |  |  |
|          |           |                 |                 | 7.0           | 92   | 90 | 88 | 86 | 86 | 84   | 82 | 80 | 74 | 72 | 71   | 70 | 62 | 61 | 60 | 59   | 44  |  |  |      |     |  |  |
|          |           |                 |                 | 10.0          | 94   | 92 | 91 | 89 | 87 | 86   | 85 | 83 | 75 | 74 | 73   | 72 | 64 | 63 | 62 | 61   | 46  |  |  |      |     |  |  |

