

屋内照明器具特性	
品番 (品名)	XLGB82800
光源	LED5000_70_400 ×1 400.0 lm
管理番号	K0171431 (0) DB 1
BZ分類	BZ9 / 0.7 / BZ8

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		44 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		56 %																								
保守率		良 中 否	0.63	0.6	45	33	25	19	42	30	23	18	35	26	20	15	29	21	16	13	8					
			0.6	0.8	54	41	33	27	49	38	31	25	41	33	26	21	34	27	22	18	12					
			0.56	1.0	60	48	39	33	55	44	37	31	46	38	31	26	38	31	26	22	15					
				1.25	65	54	46	39	60	50	43	37	51	43	37	32	42	36	31	27	18					
下方投影面積		cm ²		1.5	69	59	51	44	64	55	47	42	54	47	41	36	45	39	34	30	21					
等価発光面積			cm ²	2.0	75	66	59	52	69	61	55	49	59	52	47	43	49	44	40	36	26					
取付 高さ	器具間隔最大限			2.5	79	71	64	58	73	66	60	54	62	56	52	47	52	47	44	40	29					
	横方向 (A)		縦方向 (B)	3.0	81	74	68	63	76	69	64	59	64	59	55	51	54	50	47	43	32					
H m	1.61 H m	1.66 H m		4.0	85	79	74	69	79	74	69	65	68	64	60	56	57	54	51	48	35					
				5.0	87	82	77	73	81	77	72	69	70	66	63	60	59	56	54	51	38					
				7.0	90	86	82	79	84	80	77	74	73	70	67	64	62	59	57	55	42					
				10.0	92	89	86	83	86	83	81	78	75	73	70	68	64	62	60	59	45					

