

屋内照明器具特性

品番（品名）	X L G E 7 1 1 1
光源	L E D 2 7 0 0 _ 7 0 _ 2 1 5 x 1 2 1 5 . 0 l m
管理番号	K 0 1 4 7 8 5 8 (0) D B 1
B Z 分類	B Z 4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束		32 %		床	10 %				10 %				10 %				10 %				0 %	
下方光束		68 %		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	55	44	37	32	52	42	36	31	47	39	33	29	42	35	31	27	23		
	中	0.6	0.8	64	54	47	42	61	51	45	40	55	47	42	38	49	43	39	35	30		
	否	0.56	1.0	70	61	54	49	67	58	52	47	60	53	48	44	54	48	44	41	35		
下方投影面積		cm ²	1.25	76	67	61	56	72	64	58	54	65	59	54	50	58	53	49	46	40		
			1.5	80	72	66	61	76	69	63	59	68	63	58	55	61	57	53	50	43		
等価発光面積		cm ²	2.0	85	78	73	69	80	75	70	66	72	68	64	61	65	62	59	56	48		
取付	器具間隔最大限		2.5	88	82	78	74	84	79	75	71	75	72	68	65	68	65	62	60	52		
高さ	横方向 (A) 縦方向 (B)		3.0	90	85	81	78	86	81	78	75	77	74	71	69	69	67	65	63	54		
H _m	0.00 H _m	0.00 H _m	4.0	93	89	86	83	88	85	82	79	80	77	75	73	72	70	68	66	57		
			5.0	94	91	88	86	90	87	85	82	81	79	77	75	73	72	70	69	59		
			7.0	96	94	92	90	92	90	88	86	83	82	80	79	75	74	73	72	61		
			10.0	98	96	94	93	93	92	90	89	84	83	82	81	76	75	75	74	63		

