

屋内照明器具特性	
品番 (品名)	XLH1560UL
光源	LED3000_85_1370 x1 1370.0 lm
管理番号	K0173385 (0) DB 1
BZ分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %						
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %						
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %						
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M			
下方光束		1 0 0 %																									
保守率		良	0 . 6	7 5	6 7	6 2	5 8	7 4	6 7	6 2	5 8	7 2	6 6	6 1	5 8	7 1	6 5	6 1	5 8	5 7							
		中	0 . 8	8 3	7 5	7 0	6 7	8 2	7 5	7 0	6 7	8 0	7 4	7 0	6 6	7 8	7 3	6 9	6 6	6 5							
		否	0 . 7 2	8 7	8 1	7 6	7 3	8 6	8 0	7 6	7 2	8 4	7 9	7 5	7 2	8 2	7 8	7 4	7 2	7 0							
			0 . 6 8	1 . 2 5	9 1	8 6	8 1	7 8	9 0	8 5	8 1	7 8	8 8	8 4	8 0	7 7	8 6	8 2	7 9	7 7	7 5						
下方投影面積		c m ²	1 . 5	9 4	8 9	8 5	8 2	9 3	8 8	8 5	8 1	9 1	8 7	8 4	8 1	8 9	8 5	8 3	8 0	7 8							
等価発光面積			c m ²	2 . 0	9 8	9 4	9 0	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 6	9 2	9 0	8 7	8 5	8 3						
取付 高さ	器具間隔最大限		2 . 5	1 0 0	9 6	9 3	9 1	9 9	9 5	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 6							
	横方向 (A)	縦方向 (B)	3 . 0	1 0 1	9 8	9 6	9 3	1 0 0	9 7	9 5	9 3	9 8	9 6	9 3	9 2	9 6	9 4	9 2	9 1	8 8							
H _m	0 . 3 7 H _m	0 . 8 4 H _m	4 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 6	9 5	9 3	9 1							
			5 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3							
			7 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5							
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 6							

