

# 屋内照明器具特性

|         |                              |          |
|---------|------------------------------|----------|
| 品番 (品名) | SLB15785 + SLK22000 + SLK290 |          |
| 光源      | LLD3401LCB1 ×1               | 700.0 lm |
| 管理番号    | K0193683 (0) DB 1            |          |
| BZ分類    | BZ2 / 1.8 / BZ3 / 8.5 / BZ4  |          |

|        |                 |         |             |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |     |
|--------|-----------------|---------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|-----|
| 器具効率   | 91%             | 天井      | 80%         |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0% |     |
|        | 上方光束<br>9%      |         | 下方光束<br>82% | 壁  | 70 | 50 | 30  | 10 | 70 | 50 | 30  | 10 | 70 | 50 | 30  | 10 | 70 | 50 | 30 | 10  |
| 室指数    | 照明率 ( X0.01 )   |         |             |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    | ZCM |
| 保守率    | 良               | 0.63    | 0.6         | 60 | 51 | 45 | 41  | 58 | 50 | 45 | 41  | 56 | 49 | 44 | 41  | 53 | 47 | 43 | 40 | 38  |
|        | 中               | 0.6     | 0.8         | 68 | 60 | 54 | 50  | 66 | 59 | 53 | 49  | 63 | 57 | 52 | 49  | 60 | 55 | 51 | 48 | 45  |
|        | 否               | 0.56    | 1.0         | 73 | 65 | 60 | 56  | 71 | 64 | 59 | 55  | 68 | 62 | 57 | 54  | 65 | 60 | 56 | 53 | 50  |
|        |                 |         | 1.25        | 77 | 70 | 65 | 61  | 75 | 69 | 64 | 60  | 72 | 66 | 62 | 59  | 68 | 64 | 61 | 58 | 55  |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5         | 80 | 74 | 69 | 65  | 78 | 72 | 68 | 64  | 74 | 70 | 66 | 63  | 71 | 67 | 64 | 61 | 58  |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0         | 84 | 79 | 74 | 71  | 82 | 77 | 73 | 70  | 78 | 74 | 71 | 68  | 74 | 71 | 69 | 66 | 63  |
| 取付高さ   | 器具間隔最大限         |         | 2.5         | 86 | 82 | 78 | 75  | 84 | 80 | 77 | 74  | 80 | 77 | 74 | 72  | 77 | 74 | 72 | 69 | 66  |
|        | 横方向 (A)         | 縦方向 (B) | 3.0         | 88 | 84 | 81 | 78  | 86 | 82 | 79 | 76  | 82 | 79 | 76 | 74  | 78 | 76 | 74 | 72 | 68  |
| Hm     | 0.62Hm          | 0.62Hm  | 4.0         | 90 | 87 | 84 | 81  | 88 | 85 | 82 | 80  | 84 | 81 | 79 | 77  | 80 | 78 | 76 | 75 | 71  |
|        |                 |         | 5.0         | 91 | 89 | 86 | 84  | 89 | 87 | 84 | 82  | 85 | 83 | 81 | 80  | 81 | 80 | 78 | 77 | 72  |
|        |                 |         | 7.0         | 93 | 91 | 89 | 87  | 91 | 89 | 87 | 85  | 87 | 85 | 84 | 82  | 83 | 82 | 80 | 79 | 75  |
|        |                 |         | 10.0        | 94 | 92 | 91 | 90  | 92 | 90 | 89 | 88  | 88 | 87 | 86 | 85  | 84 | 83 | 82 | 81 | 77  |

