

# 屋内照明器具特性

品番 (品名)	SLB15785 + SLK22000 + SLK290	
光源	LLD3401LCB1 ×1                      700.0 1 m	
管理番号	K0192481 (1) DR 1	
BZ分類	BZ1	

器具効率	38 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %				
下方光束	38 %		床	10 %				10 %				10 %				10 %				0 %			
		室指数	照明率 ( X0.01)																				ZCM
保守率	良	0.67	0.6	31	29	27	26	31	29	27	26	30	28	27	26	30	28	27	26	26			
	中	0.63	0.8	34	32	30	29	34	32	30	29	33	31	30	29	32	31	30	29	28			
	否	0.56	1.0	35	34	32	31	35	33	32	31	34	33	32	31	34	33	32	31	30			
			1.25	37	35	34	33	36	35	34	33	36	34	33	32	35	34	33	32	32			
下方投影面積	c m <sup>2</sup>		1.5	37	36	35	34	37	36	35	34	36	35	34	34	36	35	34	33	33			
	等価発光面積		c m <sup>2</sup>	2.0	38	37	36	35	38	37	36	35	37	36	36	35	37	36	35	35	34		
取付高さ	器具間隔最大限		2.5	39	38	37	36	39	38	37	36	38	37	36	37	36	36	35	35	35			
	横方向 (A)	縦方向 (B)	3.0	39	38	38	37	39	38	37	37	38	38	37	36	37	37	36	36	35			
H m	0.87 H m	0.86 H m	4.0	40	39	39	38	39	39	38	38	39	38	38	37	38	37	37	37	36			
			5.0	40	40	39	39	40	39	39	38	39	38	38	38	38	38	37	37	36			
			7.0	40	40	40	39	40	40	39	39	39	39	39	39	38	38	38	38	37			
			10.0	41	40	40	40	40	40	40	40	39	39	39	39	39	39	38	38	37			

