

屋内照明器具特性

品番 (品名)	SLB15785+SLK22001+SLK290	
光源	LLD2401LCB1 ×1 500.0 lm	
管理番号	K0193060(0)DB1	
BZ分類	BZ6	

器具効率	82%	天井	80%				70%				50%				30%				0%		
	上方光束		25%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		57%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	0.6	4.2	3.2	2.6	2.1	4.0	3.1	2.5	2.1	3.5	2.8	2.3	1.9	3.1	2.5	2.1	1.8	1.5
	中	0.6	0.6	0.6	4.9	3.9	3.3	2.8	4.6	3.7	3.1	2.7	4.1	3.4	2.9	2.5	3.6	3.1	2.6	2.3	1.9
	否	0.56	0.56	0.56	5.4	4.4	3.8	3.3	5.1	4.2	3.6	3.2	4.5	3.8	3.3	2.9	4.0	3.4	3.0	2.7	2.2
	0.56	0.56	0.56	5.8	5.0	4.3	3.8	5.5	4.7	4.1	3.7	4.9	4.2	3.8	3.4	4.3	3.8	3.4	3.1	2.6	2.6
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	35.0	40.0	45.0
	等価発光面積		c m ²	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	35.0	40.0	45.0
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0
	横方向 (A)	縦方向 (B)	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0	65.0
H m	0.94 H m	0.94 H m	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0	65.0	70.0
			5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0	65.0	70.0	75.0
			7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0
			10.0	12.5	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0	90.0	95.0

