

屋内照明器具特性

| | | |
|---------|------------------------------|----------|
| 品番 (品名) | SLB15785 + SLK22001 + SLK290 | |
| 光源 | LLD3411LCB1 ×1 | 700.0 1m |
| 管理番号 | K0192482 (1) DR 1 | |
| BZ分類 | BZ1 | |

| | | | | | | | | | | | | | | | | | | | | |
|------------------|------------------|---------|------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
| 器具効率 | 75 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | 上方光束 0 % | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % |
| 下方光束 | 75 % | 床 | | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.67 | 0.6 | 62 | 58 | 55 | 53 | 62 | 58 | 55 | 53 | 61 | 57 | 55 | 53 | 60 | 57 | 54 | 53 | 52 |
| | 中 | 0.63 | 0.8 | 67 | 63 | 61 | 59 | 67 | 63 | 60 | 59 | 66 | 62 | 60 | 58 | 65 | 62 | 60 | 58 | 57 |
| | 否 | 0.56 | 1.0 | 70 | 67 | 64 | 62 | 69 | 66 | 64 | 62 | 68 | 65 | 63 | 62 | 67 | 65 | 63 | 62 | 61 |
| 下方投影面積 等価発光面積 | c m ² | 1.25 | 72 | 69 | 67 | 65 | 72 | 69 | 67 | 65 | 70 | 68 | 66 | 65 | 69 | 67 | 66 | 64 | 63 | |
| | | 1.5 | 74 | 71 | 69 | 67 | 73 | 71 | 69 | 67 | 72 | 70 | 68 | 67 | 71 | 69 | 67 | 66 | 65 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 77 | 75 | 73 | 72 | 76 | 74 | 73 | 72 | 75 | 73 | 72 | 71 | 73 | 72 | 71 | 70 | 69 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 77 | 76 | 75 | 73 | 77 | 75 | 74 | 73 | 75 | 74 | 73 | 72 | 74 | 73 | 72 | 71 | 70 |
| H m | 0.71H m | 0.71H m | 4.0 | 78 | 77 | 76 | 75 | 78 | 76 | 75 | 75 | 76 | 75 | 74 | 74 | 75 | 74 | 73 | 73 | 71 |
| | | | 5.0 | 79 | 78 | 77 | 76 | 78 | 77 | 76 | 76 | 76 | 76 | 75 | 75 | 75 | 74 | 74 | 73 | 72 |
| | | | 7.0 | 79 | 79 | 78 | 77 | 79 | 78 | 77 | 77 | 77 | 77 | 76 | 76 | 76 | 75 | 75 | 74 | 72 |
| | | | 10.0 | 80 | 79 | 79 | 78 | 79 | 79 | 78 | 78 | 77 | 77 | 77 | 76 | 76 | 76 | 75 | 75 | 73 |

