

# 屋内照明器具特性

品番 (品名)	SLB15785 + SLK22002 + SLK290	
光源	LLD2421LCB1 ×1                      500.0 1m	
管理番号	K0193682 (0) DB1	
BZ分類	BZ1/1.4 / BZ2/4.5 / BZ3	

器具効率	97%	天井	80%				70%				50%				30%				0%																																																																																																																																																																											
	上方光束		12%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																																																																																																																																																									
下方光束	85%	床	10%				10%				10%				10%				0%																																																																																																																																																																											
室指数	照明率 ( X0.01 )																			ZCM																																																																																																																																																																										
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6																																																																																																																																																																										
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6																																																																																																																																																																										
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56																																																																																																																																																																										
下方投影面積	等価発光面積	c m <sup>2</sup>		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0																																																																																																																																																																																		
		c m <sup>2</sup>		84	87	90	92	94	96	97	98	99	69	76	80	84	87	90	92	94	96	97	98	99	61	68	73	78	81	85	88	90	91	92	93	95	53	60	65	69	73	76	77	78	82	84	86	88	68	72	75	78	80	81	82	83	86	87	88	89	60	63	64	67	69	70	71	72	75	77	78	80	52	59	64	69	72	73	74	75	78	79	80	81	65	71	75	78	80	81	82	83	86	87	88	89	59	65	70	74	77	78	79	80	83	84	85	86	55	61	66	70	73	74	75	76	79	80	81	82	52	58	63	67	70	71	72	73	76	77	78	79	62	68	72	75	77	78	79	80	83	84	85	86	57	63	67	71	73	74	75	76	79	80	81	82	54	60	64	67	70	71	72	73	76	77	78	79	51	57	61	64	66	67	68	69	72	73	74	75	49	55	59	62	64	65	66	67	70	71
取付高さ	器具間隔最大限		H m		0.53 H m		0.53 H m																																																																																																																																																																																							
横方向 (A)	縦方向 (B)																																																																																																																																																																																													

