

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22002 + SLK290									
光源	LLD3421LCB1 ×1 700.0 1 m									
管理番号	K0193059 (0) DB 1									
BZ分類	BZ4 / 0.7 / BZ5 / 3.5 / BZ6									

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %						
	上方光束		25 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
	下方光束		62 %		床	10 %				10 %				10 %				10 %				0 %			
室指数	照明率 (X0.01)																				ZCM				
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6				
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6				
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56				
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56				
下方投影面積	c m ²		1.25	63	55	48	43	60	52	46	42	54	48	43	39	48	43	39	48	43	39	36	31	28	24
	等価発光面積		c m ²	1.5	66	59	53	48	63	56	50	46	57	51	46	43	51	46	42	48	43	39	33	28	24
取付高さ	器具間隔最大限		2.5	74	68	63	58	70	65	60	56	63	59	55	52	57	53	50	57	53	50	48	44	41	37
	横方向 (A)	縦方向 (B)	3.0	76	70	66	62	72	67	63	59	65	61	58	55	61	58	55	61	58	55	50	46	43	39
H m	0.49 H m	0.49 H m	4.0	78	74	70	67	75	71	67	64	67	64	61	59	61	58	56	61	58	56	54	50	46	42
			5.0	80	76	73	70	76	73	70	67	69	66	64	62	62	60	58	62	60	58	56	52	48	44
			7.0	82	79	77	74	78	76	73	71	71	69	67	65	64	63	61	64	63	61	59	56	53	49
			10.0	84	82	80	78	80	78	76	74	73	71	70	68	66	65	63	66	65	63	61	58	55	51

