

# 屋内照明器具特性

品番 (品名)	SLB15785 + SLK22002 + SLK290	
光源	LLD2411LCB1 ×1	500.0 l m
管理番号	K0192485 (1) DR 1	
BZ分類	BZ1	

器具効率	75 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	75 %		室指数		照明率 ( X0.01 )															
保守率	良 0.67	0.6	63	58	55	53	62	58	55	53	61	58	55	53	60	57	55	53	52	
	中 0.63	0.8	68	64	61	59	67	63	61	59	66	63	60	59	65	62	60	59	58	
	否 0.56	1.0	71	67	64	63	70	67	64	62	69	66	64	62	68	65	63	62	61	
下方投影面積	c m <sup>2</sup>	1.25	73	70	67	66	72	69	67	66	71	68	67	65	70	68	66	65	64	
		1.5	74	72	70	68	74	71	69	68	72	70	68	67	71	69	68	67	65	
等価発光面積	c m <sup>2</sup>	2.0	76	74	72	71	75	73	72	70	74	72	71	70	73	71	70	69	68	
		2.5	77	75	74	73	76	75	73	72	75	74	72	71	74	72	72	71	69	
取付高さ	器具間隔最大限		3.0	78	76	75	74	77	76	74	73	76	74	73	73	74	73	72	70	
H m	横方向 (A)	縦方向 (B)	4.0	79	78	77	76	78	77	76	75	76	76	75	74	75	74	74	73	
	0.70 H m	0.70 H m	5.0	79	78	77	77	79	78	77	76	77	76	76	75	75	75	74	74	
			7.0	80	79	79	78	79	78	78	77	78	77	77	76	76	76	75	73	
			10.0	80	80	79	79	80	79	79	78	78	78	77	77	76	76	76	74	

