

# 屋内照明器具特性

品番 (品名)	SLB15785 + SLK22003 + SLK290				
光源	LLD3401LCB1 ×1                      700.0 1 m				
管理番号	K0193243 (0) DB 1				
BZ分類	BZ3 / 0.9 / BZ4 / 3.5 / BZ5				

器具効率	82 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		16 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		66 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	0.6	48	40	34	30	47	39	33	30	43	36	32	29	40	35	31	28	25
	中	0.6	0.6	0.6	55	47	41	37	53	46	40	36	49	43	39	35	46	41	37	34	31
	否	0.56	0.56	0.56	60	52	47	42	58	51	45	41	53	48	43	40	50	45	41	38	35
					64	57	52	47	62	55	50	46	57	52	48	44	53	49	45	42	38
下方投影面積	c m <sup>2</sup>		1.25	64	57	52	47	62	55	50	46	57	52	48	44	53	49	45	42	38	
	等価発光面積		c m <sup>2</sup>	1.5	67	60	55	51	64	58	54	50	60	55	51	48	55	51	48	45	41
取付高さ	器具間隔最大限		2.0	71	65	61	57	68	63	59	56	63	59	56	53	59	55	53	50	45	
	H m	横方向 (A)	縦方向 (B)	2.5	73	68	64	61	71	66	63	59	66	62	59	56	61	58	55	53	48
1.06 H m		1.06 H m	3.0	75	71	67	64	72	68	65	62	67	64	61	59	62	60	58	56	50	
			4.0	77	74	71	68	75	71	69	66	69	67	65	62	64	62	61	59	53	
			5.0	79	76	73	71	76	73	71	69	71	69	67	65	66	64	62	61	55	
			7.0	80	78	76	74	78	76	74	72	72	71	69	68	67	66	65	64	57	
			10.0	82	80	78	77	79	77	76	75	74	72	71	70	69	68	67	66	59	

