

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22003 + SLK290	
光源	LLD2401LCB1 ×1 500.0 lm	
管理番号	K0193060 (0) DB1	
BZ分類	BZ6	

器具効率	82%	天井	80%				70%				50%				30%				0%			
	上方光束		25%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	下方光束		57%		床	10%				10%				10%				10%				0%
室指数	照明率 (×0.01)																			ZCM		
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6		
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6		
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56		
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56		
下方投影面積	c m ²		1.25	58	50	43	38	55	47	41	37	49	42	38	34	43	38	34	31	26	23	19
	等価発光面積		c m ²	1.5	61	53	47	42	58	51	45	41	51	46	41	37	46	41	37	34	28	24
取付高さ	器具間隔最大限		2.5	68	62	57	53	65	59	55	51	58	54	50	46	52	48	45	42	35	31	26
	横方向 (A)	縦方向 (B)	3.0	71	65	60	56	67	62	58	54	60	56	52	49	53	50	47	45	38	34	29
H m	0.94 H m	0.94 H m	4.0	73	69	65	61	70	65	62	59	62	59	56	54	56	53	51	49	41	38	34
			5.0	75	71	68	64	71	68	65	62	64	61	59	56	57	55	53	51	43	40	36
			7.0	77	74	71	69	73	71	68	66	66	64	62	60	59	58	56	54	46	43	39
			10.0	79	76	74	72	75	73	71	69	68	66	65	63	61	60	58	57	48	45	41

