

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22003 + SLK290				
光源	LLD2411LCB1 ×1 500.0 lm				
管理番号	K0193061 (0) DB 1				
BZ分類	BZ4/0.7/BZ5/3.5/BZ6				

器具効率	89%	天井	80%				70%				50%				30%				0%		
	上方光束		26%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		63%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	65	56	50	45	62	54	48	43	55	49	44	40	50	45	41	37	32	
	等価発光面積	c m ²		1.5	68	60	54	49	65	58	52	47	58	52	48	44	52	48	44	41	35
取付高さ		器具間隔最大		2.5	76	70	65	60	72	66	62	58	65	61	57	53	58	55	52	49	42
	H m	横方向 (A)	縦方向 (B)	3.0	78	72	68	64	74	69	65	61	67	63	59	56	60	57	54	52	44
H m		0.60 H m	0.60 H m	4.0	80	76	72	68	77	73	69	66	69	66	63	61	62	60	58	55	47
	H m			5.0	82	78	75	72	78	75	72	69	71	68	66	63	64	62	60	58	50
7.0				84	81	78	76	80	78	75	73	73	71	69	67	66	64	63	61	52	
H m				10.0	86	83	81	79	82	80	78	76	75	73	71	70	68	66	65	64	55

