

# 屋内照明器具特性

品番 (品名)	SLB15785 + SLK22004	
光源	LLD3411LCB1 ×1	700.0 1m
管理番号	K0192996 (0) DB1	
BZ分類	BZ1	

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	98 %		室指数	照明率 ( X0.01 )																ZCM
保守率	良 0.67	0.6	0.6	88	83	81	79	87	83	80	78	86	83	80	78	85	82	80	78	77
	中 0.63		0.8	93	88	86	84	92	88	86	84	91	87	85	83	89	87	85	83	82
	否 0.56		1.0	95	92	89	87	95	91	89	87	93	90	88	87	92	90	88	86	85
下方投影面積	cm <sup>2</sup>	1.25	1.25	97	94	92	90	97	94	92	90	95	93	91	89	94	92	90	89	88
			1.5	99	96	94	92	98	95	93	92	96	94	93	91	95	93	92	91	89
等価発光面積	cm <sup>2</sup>	2.0	2.0	101	98	97	95	100	98	96	95	98	96	95	94	97	95	94	93	91
			2.5	102	100	98	97	101	99	98	96	99	98	96	95	97	96	95	94	93
取付高さ	器具間隔最大限		3.0	103	101	99	98	102	100	99	98	100	98	97	96	98	97	96	95	93
	横方向 (A)	縦方向 (B)		4.0	103	102	101	100	102	101	100	99	100	100	99	98	99	98	97	97
Hm	0.76Hm	0.76Hm	5.0	104	103	102	101	103	102	101	100	101	100	99	99	99	98	98	97	95
			7.0	105	104	103	102	104	103	102	102	102	101	100	100	100	99	99	98	96
			10.0	105	105	104	104	104	104	103	103	102	102	101	101	100	100	99	99	96

