

屋内照明器具特性

| | | |
|---------|--|--|
| 品番 (品名) | SLB15785 + SLK22004 + SLK290 | |
| 光源 | LLD2421LCB1 ×1 500.0 lm | |
| 管理番号 | K0193248 (0) DB1 | |
| BZ分類 | BZ2/1.1/BZ3/6.0/BZ4 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|-----------------|-----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|-----|
| 器具効率 | 86% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 | | 15% | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| | 下方光束 | | 71% | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.63 | 0.6 | 54 | 46 | 41 | 37 | 53 | 45 | 40 | 37 | 50 | 43 | 39 | 36 | 47 | 41 | 38 | 35 | 32 | |
| | 中 | 0.6 | 0.8 | 62 | 54 | 48 | 44 | 60 | 52 | 47 | 44 | 56 | 50 | 46 | 43 | 53 | 48 | 44 | 41 | 39 | |
| | 否 | 0.56 | 1.0 | 66 | 59 | 54 | 50 | 64 | 57 | 53 | 49 | 60 | 55 | 51 | 47 | 57 | 52 | 49 | 46 | 43 | |
| | | | 1.25 | 70 | 64 | 59 | 55 | 68 | 62 | 57 | 54 | 64 | 59 | 55 | 52 | 60 | 56 | 53 | 50 | 47 | |
| 下方投影面積 | cm ² | | 1.5 | 73 | 67 | 62 | 59 | 71 | 65 | 61 | 58 | 66 | 62 | 58 | 55 | 62 | 59 | 56 | 53 | 50 | |
| | 等価発光面積 | | cm ² | 2.0 | 77 | 72 | 68 | 64 | 74 | 70 | 66 | 63 | 70 | 66 | 63 | 60 | 66 | 63 | 60 | 58 | 54 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 79 | 75 | 71 | 68 | 77 | 73 | 69 | 67 | 72 | 69 | 66 | 64 | 68 | 65 | 63 | 61 | 56 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 81 | 77 | 74 | 71 | 78 | 75 | 72 | 69 | 74 | 71 | 68 | 66 | 69 | 67 | 65 | 63 | 58 | |
| Hm | 0.64Hm | 0.64Hm | 4.0 | 83 | 80 | 77 | 75 | 80 | 78 | 75 | 73 | 76 | 73 | 71 | 70 | 71 | 69 | 68 | 66 | 61 | |
| | | | 5.0 | 84 | 82 | 79 | 77 | 82 | 79 | 77 | 75 | 77 | 75 | 73 | 72 | 72 | 71 | 69 | 68 | 63 | |
| | | | 7.0 | 86 | 84 | 82 | 80 | 83 | 81 | 80 | 78 | 78 | 77 | 76 | 74 | 74 | 73 | 71 | 71 | 65 | |
| | | | 10.0 | 87 | 85 | 84 | 83 | 84 | 83 | 82 | 81 | 79 | 78 | 77 | 76 | 75 | 74 | 73 | 72 | 66 | |

