

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22004 + SLK290	
光源	LLD3411LCB1 ×1	700.0 1m
管理番号	K0193684 (0) DB1	
BZ分類	BZ1	

器具効率	98%	天井	80%				70%				50%				30%				0%				
	上方光束 7%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	91%	床		10%				10%				10%				10%				0%			
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6			
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6			
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56			
下方投影面積	等価発光面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	83	87	90	92	94	96	98	99	100	101	102
		cm ²		1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	85	89	93	96	99	100	100	99	98	96	94	92
取付高さ	器具間隔最大限		Hm		0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	
	器具間隔最大限		Hm		0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm	0.75Hm

