

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22004 + SLK290	
光源	LLD3411LCB1 ×1 700.0 lm	
管理番号	K0193058 (0) DB 1	
BZ分類	BZ5 / 2.8 / BZ6	

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %												
	上方光束 26 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %											
下方光束	62 %	床		10 %				10 %				10 %				10 %				0 %											
室指数	照明率 (X0.01)																				ZCM										
保守率	良 中 否	0.63	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	47	37	31	26	45	36	30	26	40	33	28	24	36	30	26	23	19
		0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	54	45	38	33	51	43	37	32	46	39	34	30	41	36	31	28	24	
		0.56	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	59	50	43	38	56	48	42	37	50	44	38	35	45	40	35	32	27		
		0.56	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	64	55	49	44	60	53	47	42	54	48	43	39	48	43	39	43	39	36	31	
下方投影面積	cm ²		1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	67	59	53	48	64	56	51	46	57	51	47	43	51	46	43	39	34				
等価発光面積	cm ²		2.0	2.5	3.0	4.0	5.0	7.0	10.0	71	65	59	54	68	62	57	52	61	56	52	48	55	51	47	44	38					
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	74	68	63	59	71	65	61	57	64	59	56	52	57	54	51	48	41						
	横方向 (A)	縦方向 (B)	3.0	4.0	5.0	7.0	10.0	76	71	66	62	73	68	64	60	65	62	58	55	59	56	53	51	43							
Hm	0.60Hm	0.60Hm	4.0	5.0	7.0	10.0	79	75	71	67	75	71	68	65	68	65	62	59	61	59	56	54	46								
			5.0	7.0	10.0	81	77	74	71	77	74	71	68	70	67	64	62	63	61	59	57	48									
			7.0	10.0	83	80	77	75	79	76	74	72	72	70	68	66	65	63	61	60	51										
			10.0	85	82	80	78	81	79	77	75	73	72	70	69	66	65	64	63	54											

